The Chemical

NEW PLANT OPENED

(See page 245)

"Fluor acid air is procured by dissolving the earthy substance called fluor in vitriolic acid.

This kind of air extinguishes a candle and, like vitriolic air, one measure of it saturates two of alkaline air. It is peculiar to this kind of air to dissolve glass when it is hot.

It seems to consist of a peculiar acid vapour, united to the strong substance of the fluor; for water being admitted to it absorbs the acid vapour, and the stony substance is deposited. By this means it exhibits an amusing appearance, whether water be admitted to a glass jar previously filled with that air, or the bubbles of air be admitted, as they are formed, to a quantity of water resting on mercury."



... an amusing appearance

So, in 1797, Joseph Priestley described his early observations on hydrofluoric acid to students at the New College in Hackney, and recorded them under the title of *Heads of Lectures on a Course of Experimental Philosophy*. Today, using fluor acid air dissolved in aqua destillata, and costly vessels of silver and platinum, B.D.H. chemists make vast quantities of

a great variety of fluorides of high purity, free from all stony substances, for which the B.D.H. sales departments will happily quote for deliveries by the pound, the cwt. or the ton.

Such fluorides are used industrially for all sorts of purposes from increasing the light transmitting properties of lenses to aiding the production of atomic energy.

B.D.H. LABORATORY CHEMICALS

THE BRITISH DRUG HOUSES LTD. B.D.H. LABORATORY CHEMICALS GROUP POOLE DORSET

IT'S PART OF THE NORTHIDE SERVICE

Win your battle against ACCIDENTS

NORTH P.V.C. Caps and Headgear are scientifically designed to afford complete protection against a wide variety of industrial hazards. They are resistant to chemicals, are hard wearing, comfortable and offer improved ventilation. A full range, available in standard colours and sizes, includes F.S.3 Cap with fixed Visor and Neck Cover, illustrated above right, and F.S.2 Cap with Neck and Shoulder Coverage, fixed Visor and Front Apron, illustrated below right.

Quick deliveries of standard range are assured—it's part of the Northide Service.





Send for Leaflets

describing P.V.C. Gloves, Garments, Headgear, etc. also Leather and Cotton Safety Gloves, Dankey Jackets and Safety Boots.

NORTHIDE LTD

IMPERVIA WORKS, QUEEN STREET, STOCKPORT, CHESHIRE. Tel. STOCKPORT 2425 (2 lines)
Warehouses in Stockport, London and Birmingham

REGD. TRADE MARK

Impervious &

Corrosion Resistant GLOBE VALVES

RESISTANT TO PRACTICALLY ALL CORROSIVE CHEMICALS . UNAFFECTED BY SEVERE THERMAL SHOCK · CORROSIVE FLUIDS IN CONTACT WITH "KARBATE" IMPERVIOUS GRA-PHITE THROUGHOUT . LIGHT AND SMALL. SHORT FACE-TO-FACE DIMENSIONS, SELF LUBRICATING. AVAILABLE IN 1" AND 2" SIZES.

PIPES AND FITTINGS

Also available in the same anti-corrosive material are "Karbate" pipes and fittings, which cover a wide range of pipe diameters, block elbows, tee pieces, solid and flexible couplings etc.

Send us details of your corrosive fluid handling problem and we will gladly assist you.

16mm.Talkie Colour Films describing the value of "KARBATE" to the Chemical Industry available for showing on request.

TISH ACHESON ELECTRODES LIMITED

GRANGE MILL LANE . WINCOBANK . SHEFFIELD

Telephone: ROTHERHAM 4836 (4 lines)

BRITAIN'S LARGEST MANUFACTURERS OF GRAPHITE ELECTRODES & ANODES

INDEX TO ADVERTISERS

The first figures refer to advertisement in The Chemical Age Year Book, the second to the current issue

age		Page	Page	Policies V and Mills Lad	age	Page		Page
83	A.P.V. Co., Ltd., The			British Lead Mills Ltd.		250	Dowlow Lime & Stone Co.,	
16	Acalor (1948) Ltd.	-		British Resin Products Ltd.	-		Ltd., The	-
77	Accrington Brick & Tile Co.,		372	British Railway Traffic &	- 1		Dring & Fage Ltd.	-
	Ltd., The			Electric Co., Ltd.	-	258	Drummond Patents Ltd.	-
29	Adequate Weighers Ltd.		256	British Rototherm Co. Ltd. The	-	257	Dryden, T., Ltd.	_
70	Aimer Products Ltd.	-	166	British Steam Specialties Ltd.	-	280	E.C.D., Ltd.	
58	Albany Engineering Co. Ltd. The	-	236	British Tar Products Ltd.	-		Edison Swan Electric Co., Ltd.	_
94	Alcock (Peroxice) Ltd.	_		British Thomson-Houston Co. Ltd.			Electronic Switchgear	-
	Alexander, Herbert, & Co., Ltd.		292	British Titan Products Co., Ltd.		259	Electrothermal Engineering Ltd.	
	Alginate Industries Ltd.		180	Broadbent, Thomas, & Sons, Ltd.	_		k. Elliott, H. J., Ltd.	
78	Allen, Edgar, & Co., Ltd.	_	191	Brooks & Walker Ltd.				
			209				Elliott Brothers (London) Ltd.	
0	Alumina Co., Ltd., The	-		Brotherhood, Peter, Ltd.	220		English Glass Co., Ltd., The	-
66	Amalgamated Oxides (1939) Ltd.	-	232		237		d. Erinoid Ltd.	-
36	Angel, H. Reeve, & Co., Ltd.			Brough, E. A., & Co., Ltd.		296	Evered & Co., Ltd.	No.
	Armour & Co., Ltd.	233	214	Browns Foundry Co., Ltd.	-		Ewart, M. D., & Co., Ltd.	25
Co	I. Ashmore, Benson, Pease & Co.	-	260	Brush Design Group, The	-	288	Farnell Carbons Ltd.	
19	Ashworth, Arthur, Ltd.	Person .	274	Bryan Donkin Co., Ltd., The			Fawcett Finney Ltd.	_
36	Audley Engineering Co., Ltd.	-	290	Buell (1952) Ltd.	-	228	Feltham, Walter H., & Son Ltd.	-
6	Autometric Pumps Ltd.	_	273	Burnett & Rolfe Ltd.	_	230	Ferris, J. & E., Ltd.	
	B. A. Holland Engineering		212	Bush, W. J., & Co., Ltd.		264	Film Cooling Towers (1925) Ltd.	
-	Co., Ltd., The			Butterworths Scientific Publica-		211		
	D.V. Diester Ltd						Fisher Governor & Co., Ltd.	
	B.X. Plastes Ltd.		212	tions		159	Foster Instrument Co., Ltd.	-
25	Baird & Tatlock (London) Ltd.		213	Butterfield, W. P., Ltd.		227	Foxboro-Yoxall Ltd.	-
71	Baker Perkins Ltd.	-		Calder Vale Glassworks Ltd.	-		Fraser, W. J., & Co., Ltd.	-
0	Baker Platinum Division,	- 1		Callow, F. E. (Engineers) Ltd.	234	314	Fuller's Earth Union Ltd., The	-
	Engelhard Industries Ltd.	-		Callow Rock Lime Co. Ltd. The	-	182	Gallenkamp, A., & Co., Ltd.	_
25	Balfour, Henry, & Co.	-	364	Candy Filter Co., Ltd., The			Geigy Co., Ltd., The	
22	Barclay Kellett & Co., Ltd.		264	Carbon Dioxide Co., The	_	276	Geigy Pharmaceutical Co., Ltd.	
15	Bennett, Sons & Shears Ltd.	_			236	210	General Electric Co., Ltd.	
	d. Berk, F. W., & Co., Ltd.			Cekop Trading Corporation		243		
					-		Grazebrook, M. & W., Ltd.	-
32	Beryllium & Copper Alloys		000	Chapman & Hall Ltd.	-	226	Greeff, R. W., & Co., Ltd.	-
	(Safety Tools) Ltd.		207	Chemical Workers' Union, The		222	Grindley & Co., Ltd.	4000
53		v. iii		Chemicals & Feeds Ltd.	-	226	Hackbridge & Hewittic Electric	
18	Borax Consolidated Ltd.		354		. iii		Co., Ltd.	_
	Borax & Chemicals Ltd.	236	275	Chesterfield Tube Co., Ltd., The		240	Haller & Phillips Ltd.	
37	Boulton, William, Ltd.	_	297	Ciech Ltd.	_	266	Hanovia Lamps	-
36	Bowmans Chemicals Ltd.		248	Cinema Television Ltd.		218	Harris (Lostock Gralam) Ltd.	250
90	Braby, Fredk., & Co., Ltd.		244	Clark, T. C., & Co., Ltd.	_	258	Haworth, F. (A.R.C.) Ltd.	-
31	Bramigk & Co., Ltd.		173	Clayton Dyestuffs Co. Ltd. The	_	161	Hearson, Charles, & Co., Ltd.	
52	Brannan, S., & Sons, Ltd.		176	Clayton, Son & Co., Ltd. The		220		-
		-	170		-	220	Herbert, Alfred, Ltd.	-
1	Bristol's Instrument Co., Ltd.	220	103	Clydesdale Chemical Co. Ltd. The	-		Holmes, W. C., & Co., Ltd.	-
	British Acheson Electrodes Ltd.	229	183	Cole, R. H., & Co., Ltd.		194	Honeywill & Stein Ltd.	-
32	British Arca Regulators Ltd.	-	238		237	279	Hopkin & Williams Ltd.	25
8	British Assoc, of Chemists The	-	196	Collins Improved Firebars Ltd.	-	4	Huntington, Heberlein & Co. Ltd.	
	British Carbo Norit Union Ltd.		356	Comet Pump & Eng. Co. Ltd. The	-		I.C.I. Ltd. Alkali Silicate of Soda	_
	British Ceca Co., Ltd., The			Costain-John Brown Ltd.	_		I.C.I. Limited, Billingham	
12	British Chrome & Chemicals		256	Crockatt, W., & Sons, Ltd.			I.C.I. Plastics—Darvic	
lie	Ltd. (London)		200	Cromil & Piercy Ltd.				100
4	British Chrome & Chemicals		169	Cruickshank, R., Ltd.			I.C.I. Plastics—Fluon.	-
19					-	167	Imperial Chemical Industries Ltd.	
	Ltd. (Lancs)	-	328	Cyanamid Products Ltd.		157	Imperial Smelting Corporation	
	British Drug Houses Ltd., The		250	Cyclops Engineering Co. Ltd. The			(Sales) Ltd.	*****
	front c	cover	254	Cygnet Joinery Ltd.	STREET, STREET		International Combustion	
	British Electrical Development		298	Danks of Netherton Ltd.	-		Group	Acces
	Association	231	238	Davey, Paxman & Co., Ltd.			Isopad Ltd.	-
	British Geon Limited	-		Dawson, McDonald & Dawson Ltd.		278	Jackson, Henry (Liverpool) Ltd.	-
R	British Industrial Solvents		330	Derby Luminescents Ltd.	_	382	Jackson, J. G., & Crockatt Ltd.	
	& 235 British Laboratory War	0	200	Dia Chemieausruestingen				-
14 6		0	177		220	185	Jenkins, Robert, & Co., Ltd.	-
22	Association Ltd.	-	248	Dorr-Oliver Co., Ltd. Douglas, William, & Sons Ltd.	238	187	Jenkinson, W. G., Ltd.	Acres 1
	British LaBour Pump Co., Ltd.		F/25.76	Liougias William & Sons Itd	- 1		continued on pag	~ 72

SPECIALISTS IN

BULK LIQUIDS TRANSPORT

ACIDS · OILS · SPIRITS AND GENERAL CHEMICALS


HAROLD WOOD & SONS LTD. Wormald St · Heckmondwike

Tel.: Heckmondwike 1011/5 Telegraph: 'Transport' Heckmondwike London Office: 22 South Molton St., London W.I. Tel.: Mayfair 6060



LEIGH &SONS METAL WORKS Orlande LTD. St., BOLTON

CARBOYS · PACKED CARBOYS CARBOY TILTERS AND BARROWS SAFETY CRATES TOP PROTECTORS



Hold at 1020° for 10 seconds!

From dark red to dazzling white, the colour of a heated material gives a rough and ready indication of its heat. Electro-heat is never rough but it is always ready—ready to bring the workpiece to an exact temperature for an exact period of time. And all the heat goes into the job, not into the surrounding atmosphere—which is one of the reasons why electro-heat is so economical for precise heat treatment.

In every industry, for scores of applications, electricity means higher productivity.

Electricity for Productivity

Ask your ELECTRICITY BOARD for advice and information, or get in touch with E.D.A. They can lend you, without charge, films about the uses of electricity in industry. E.D.A. are also publishing a series of books on Electricity and Productivity. Titles now available are: Electric Resistance Heating, Electric Motors and Controls, Higher Production, Lighting in Industry, and Materials Handling. Price 8/6, or 9/- post free.

issued by the British Electrical Development Association 2 Savoy Hill, London, W.C.2

INDEX TO ADVERTISERS

The first figures refer to advertisement in The Chemical Age Year Book, the second to the current issue


Page		Page	Page		
3	Jobling, James A., & Co., Ltd.			Mirrlees Watson & Co. Ltd. The — 360 Sigmund Pumps Ltd.	-
210	Johnson, G. T., & Co., Ltd.	-	260	Mirvale Chemical Co., Ltd. — Simon, Richard, & Sons, Ltd.	-
206	Johnsons of Hendon Ltd.	-	253	Mitchell, Cotts & Co., Ltd. — 320 Southern Instruments Computer	
201	Jones, Tate & Co., Ltd.	Access		Mond Nickel Co., Ltd., The Division	, marine
216	K.D.G. Instruments Ltd.			Monsanto Chemicals Ltd. — Soyozchimexport (Moscow)	_
266		_		Moore, W. & E., Ltd. — 348 Spencer Chapman & Messel Ltd.	_
200	K.W. Chemicals Ltd.	_	196		-
	Kaylene (Chemicals) Ltd.	- Ordina		Co., Ltd. Stabilag Co., Ltd., The	266
2	Keith Blackman Ltd.	-		Morgan Crucible Co., Ltd., The 404 Stanton Instruments Ltd.	200
284	Kernick & Son Ltd.	4000	252	Murphy, G. L., Ltd. – Staveley Iron & Chemical Co.Ltd.	
403	Kestner-Evaporator & Engineer-		197		
	ing Co., Ltd. co	v. iii	217		-
	Key Engineering Co. Ltd. The	-	181		234
160	Kier, J. L., & Co., Ltd.	200.00	101	Nederlandsche Verkoopkantoor — Stonehouse Paper & Bags Mills	-
288	Kingsley & Keith Ltd.	-	201	Voor Chemische Producten N.V. — Streamline Filters Ltd.	-
267	Kleen-e-ze Brush Co., Ltd.		206	Nederlandse Emballage Ondeer- Sturge, John & E., Ltd.	-
	& 269 Klinger, Richard, Ltd.	2000		neming Gebr. de Wilde N.V. — 245 Sutcliffe Speakman & Co., Ltd.	-
202			262	Negretti & Zambra Ltd. — 242 Taylor Rustless Fittings Co. Ltd.	
	Lankro Chemicals Ltd.	225	164 8	& 165 Newton Chambers & Co. Ltd. — 174 Tenaplas Sales Ltd.	-
198	Laporte Chemicals Ltd.	235		New Metals & Chemicals Ltd. — 282 Thermal Syndicate Ltd., The	
	Lavino (London) Ltd.	-	271	Nicolson, W. B. (Scientific 324 Thermix Industries Ltd.	-
221	Leda Chemicals Ltd.	-		Instruments) Ltd. — Thomason, W., & Sons Ltd.	
	Leeds & Bradford Boiler Co.,		175	Nordac Ltd. — 145 Thompson, John (Dudley) Ltd.	
	Ltd., The	proper	299	North Thames Gas Board — Thorium Ltd.	
204	Leigh & Sons Metal Works Ltd.	230	204	Northern Malleable Foundry Todd Bros. (St. Helens &	
	Leitch, John W., & Co., Ltd.	236	201	Co., Ltd., The Widnes) Ltd.	
	Lennig, Charles, & Co. (Great				-
		v. iv			
	Lennox Foundry Co., Ltd.	_	306		
	Ley. M.		300	Palfrey, William, Ltd. — 286 Tungstone Products Ltd.	-
	Light, L., & Co., Ltd.			Paper Goods Manufacturing 293 Unifloc Ltd.	-
376	Lind, Peter, & Co., Ltd.			Co., Ltd. United Coke & Chemicals Co. Ltd.	-
	er London Aluminium Co. Ltd. The			Pascall Engineering Co. Ltd. The — 172 United Filters & Engineering Ltd.	-
	London Metal Warehouses Ltd.	_	6	Paterson Engineering Co. Ltd. The — 244 W.E.X. Traders Ltd.	-
300	Longmans Green & Co., Ltd.	_	203	Peabody Ltd. — 291 Walker Extract & Chemical Co. Ltd	1
204				Penhryn Quarries Ltd. 232 Wallach Bros. Ltd.	-
204	Lord, John L., & Son	_	310 8	& 338 Permutit Co., Ltd., The — 184 Waller, George, & Son Ltd.	_
	Machinery (Continental) Ltd.	-		Pott, Cassels & Williamson 257 246 Walley, A. L.	-
	MacLellan, George, & Co., Ltd.	- 1	334	Powell Duffryn Carbon Products 190 Wallis, Charles, & Sons (Sacks) Ltd.	
199	Mallinson & Eckersley Ltd.	No.		Ltd. — Ward, Thos. W., Ltd.	
	Manesty Machines	-	G/Co	d. Power-Gas Corporation, Ltd. The — 200 Watford Chemical Co., Ltd.	_
380	Marchon Products Ltd.	240	259	Press at Coombelands, Ltd., The - 188 Watson, Laidlaw & Co., Ltd.	
263	Marco Conveyor & Eng. Co. Ltd.	-	170	Price Stutfield & Co., Ltd. — 344 Webb, William A., Ltd.	
192	Matthews & Yates Ltd.	-		Prodorite Ltd. 235 Weinreb & Randall Ltd.	
	May & Baker Ltd.		320	Production Chemicals (Rochdale) 195 Wells, A. C., & Co., Ltd.	
162	Measuring & Scientific Equip-		-	Ltd. — 224 Wengers Ltd.	
	ment Ltd.			The state of the s	_
330	Meigh Castings Ltd.				***
168		_	287		
K 11.00	Metal Containers Ltd., The		201	Reads Ltd. — Co., Ltd.	-
COV	er Metal Containers Ltd.			Richmond Welding Co., Ltd. 232 241 Wilkinson Rubber Linatex Ltd.	-
- ×	Metal Industries Ltd.	- 1	010	Robinson, F., & Co., Ltd. — 223 Willcox, W. H., & Co., Ltd.	-
n in	Metalfiltration Co., Ltd., The	-	G/Co	d. Rose, Downs & Thompson Ltd. — 214 Wilson, Edward, & Son Ltd.	-
	d. Metalock (Britain) Ltd.	-	208	Rotometer Manufacturing Co. Ltd. — 189 Winn & Coales Ltd.	-
228	Metcalf & Co.		362	St. Helens Cable & Rubber Co. Ltd. — 212 Wood, Harold, & Sons Ltd.	230
	Metropolitan - Vickers Electrical		249	Sandiacre Screw Co., Ltd., The 246 Worcester Royal Porcelain Co.,	
	Co., Ltd.		210	Scientific Glass-Blowing Co. The Ltd., The	
198		-		Shaw Petrie Ltd. — Worthington-Simpson Ltd.	
	Mills Packard Construction Co.		286	Shawinigan Ltd. — 179 Wynn (Valves) Ltd.	
	Ltd.		340	Shell Chemical Co., Ltd. — 251 Yorkshire Tar Distillers Ltd.	
261		_	247	Siebe, Gorman & Co., Ltd. — 240 Zeal, G. H., Ltd.	
	The state of the s			ATO LEGI, U. II., LIU.	

"Jullersite" SLATE FILLER

WHEREVER AN INERT FILLER
IS REQUIRED FULLERSITE
IS THE IDEAL MATERIAL

PENRHYN QUARRIES LTD.

PORT PENRHYN, BANGOR, NORTH WALES



PRESSURE VESSELS

IN STEEL
STAINLESS STEEL
ALUMINIUM
COPPER • ETC.

METAL SPRAYING
WELDING AND REPAIRS
TO ALL METALS

RICHMOND WELDING CO.


RICHMOND RD. · BRADFORD · 7

Tel: 25405

SOME OF THE

ARMOUR CHEMICALS

NOW MADE IN BRITAIN




Primary Amines RNH ₂	WHERE R IS	SOME TYPICAL APPLICATIONS	TO ASK FOR
ARMEEN 12D	pure lauryl	Intermediate for textile chemicals, quaternaries.	Armeens, L-1
ARMEEN T	technical oleyl, stearyl	Wax emulsions. Waterproofing, flotation.	F-2
ARMEEN HT	technical stearyl,	Hard rubber mould release, bitumen additive.	Armeens, L-I
ARMEEN HTD	pure stearyl,	Rubber industries. Fertilizer industry, anti-static.	L-3
ARMEEN 18D	pure stearyl	Boiler condensate control, intermediate for textile chemicals.	Armeens, L-2
ARMEEN C	pure lauryl, myristyl	Petroleum industry, corrosion inhibition. Pigment manufacture, paint industry.	G-3, G-5 L-7
Secondary Amines R ₂ NH			
ARMEEN 2C	technical lauryl, myristyl	For manufacture of quaternaries soluble in oils, etc., dispersible in water.	Armeens
ARMEEN 2HT	technical stearyl	Corrosion inhibition.	Arquads
Diamines R.NH.C ₃ H ₆ NH ₂	4		
DUOMEEN T	technical oleyl,	Road making. Paper, Waterproofing, surface coatings:	C-2/3 Duomeens
DUOMEEN CD	pure lauryl, myristyl	Epoxy resins. Corrosion inhibition.	C-3/L/I
DUOMEEN T DIOLATE	technical oleyl,	Metal working, wire drawing. Paints, caulking compounds, pigments.	G-4, L-14 L-4, L-8
Water Soluble Quaternaries [R. (CH ₃) ₃ .N] + Cl -	occary.	anita) sauteme compounts; pignostes	-,,
ARQUAD 12	pure lauryl	Foam rubber. Emulsifier.	L-5
ARQUAD IS	pure stearyl	Anti-static for plastic.	LII
ARQUAD C	technical lauryl, myristyl	Germicide, cosmetics, road emulsions. Textile industry.	E-5 G-2
Oil Soluble Water Dispersible Quaternaries [R ₂ (CH ₃) ₂ N] CI			-
ARQUAD 2C	technical lauryl, myristyl	Corrosion inhibitor, petroleum production. Internal anti-static, germicide. Insecticide and other emulsifiers. Slip aid in transparent viscose films, etc.	E-3, E-6, G-3 E-5 E-4, F-2
ARQUAD 2HT	pure stearyl, palmityl	Laundry & textile softener. Starch industry. Paper industry.	E-L E-8 E-1



★ Each of these is also available in its water-soluble acetate form: ask for booklet on ARMACS

ARMOUR & COMPANY LTD., CHEMICAL DIVISION, LINDSEY ST., LONDON, E.C.I CLERKENWELL 9011

X-ray view of DUSTLESS milling



The "Liverpool" Callow Pneumatic extractor dustless Mill possesses some unusual features. Note for instance the cast serrations at the back and front of the hood. These serrations hold the material in suspension at the hammer tips, until sufficiently ground to be removed by suction.

Incorporated in the Callow system is a pneumatic extractor which sweeps the screen with air, causing a partial vacuum in the grinding chamber. The mill is constantly under suction, thus eliminating dust in the vicinity of the grind. If you want to know how to knock the dust out of milling—


WRITE NOW FOR LITERATURE TO:-



Telephone Simonswood 2461-2

FOR FINE MILLING

FLIMINATE YOUR BOTTOM BEARINGS



BY USING THE "STOCKDALE"
TURBO AGITATOR

The specially designed Agitator by virtue of its inherent design entirely eliminates the need for the trouble-causing bottom bearing. Our Development Department will advise you on designs.

STOCKDALE ENGINEERING LIMITED

LONDON ROAD SOUTH . POYNTON . CHESHIRE

Telephone POYnton 2601/2

Organic

Peroxy

Compounds

Benzoyl Peroxide

di-t-Butyl Peroxide t-Butyl Perbenzoate t-Butyl Hydroperoxide Methyl Ethyl Ketone Peroxide Peracetic Acid

> In addition to the products shown, a number of others are in the development stage. Ask Laporte Technical Service Department for details.

Laporte Chemicals Ltd., Luton. Telephone: Luton 4390. Telegrams: Laporte, Luton




SPECIALISTS IN ALL TYPES OF ACID PROOFING



Acid - proof Tanks and Linings, Acid resisting Floor Surfaces, Neutralising Schemes, Corrosive Fume Extraction, Pipe Lines for Corrosive Fluids, Manufacturers of a complete range of Chemical Resisting Cements and Mastics









Why not consult us? HEAD OFFICE

EAGLE WORKS WEDNESBURY

TELEPHONE - WED 0284 5 LINES

LONDON OFFICE

ARTILLERY HOUSE · ARTILLERY ROW SWI TELEPHONE . ABBEY 3816 5 LINES

Fast Bases: Scarlet GGSL, RL, RCL, GL, GCL, GGL; Red BL, Red KBL, GL, GGL, 3GL, RL; Garnet GBL, GBCL; Orange GRL; Yellow GCL

Chemicals for Colour

John W. Leitch & Co. Ltd. Milnsbridge near Huddersfield

AMMONIA OXIDATION PLANT

THE AMMONIA OXIDATION UNITS FOR NITRATION IN THE SULPHURIC ACID PLANT AT THE AVENUE WERE DESIGNED, SUPPLIED AND ERECTED BY-

JOHN F. CARMICHAEL & CO. LTD.

CHEMICAL ENGINEERS & CONTRACTORS

TOWER BUILDING LIVERPOOL 3

TELEGRAMS: GAYLUSSAC LIVERPCOL TELEPHONE: CENTRAL 5265

Elemental Boron is no longer a chemical curiosity but is a commercial chemical used in the manufacture of flares, fuses, ignitors and propellants, in the production of borides for high temperature applications and with plastics for lightweight neutron shields. "TRONA" Boron is produced in several grades by American Potash & Chemical Corporation.

Enquiries to:

BORAX & CHEMICALS LIMITED KINGS BOURNE HOUSE, 229 HIGH HOLBORN, LONDON, WC.I Tel: HOLborn 6518 (PBX) Cables: BORAXCHEM LONDON

European Agents for:

AMERICAN POTASH & CHEMICAL CORPORATION

Producers of: Borax, Soda Ash, Salt Cake, Lithium, Bromine, Chlorates, Perchlorates, Manganese Dioxide and a diversified line of Agricultural and Refrigerant chemicals.



FROM
POPPING
CORN (cereals)




TO PRESERVING FRUIT


If you've a job for basic chemicals, contact

Brotherton

One of the world's largest manufacturers of hydrosulphites (hydros, formusol, redusol Z, hydros I), liquid sulphur dioxide and hexamine. Makers of metachrome and other dyestuffs (afterchrome, acid) for dyeing wool in all its forms. Other chemicals include liquor ammonia, sulphuric acid, ammonium thiosulphate, ammonium bicarbonate, sodium sulphite, bisulphite and metabisulphite.

Brotherton & Co. Ltd., P.O. Box No. 6, Leeds, 1. Telephone No. 2-9321 Telegrams Brotherton Leeds London Office: Winchester House, Old Broad Street, E.C.2, Telephone London Wall 2122





DORR-OLIVER COMPANY LIMITED

organization specializing in the design and manufacture of plant and equipment for all processes where the separation of fine solids from liquids is required.

Consult with us on your problems concerning—

AGITATION

CLASSIFICATION

CLARIFICATION

THICKENING

VACUUM AND PRESSURE FILTRATION

EFFLUENT PURIFICATION

SAND AND ACID PUMPING

MIXING ETC.

Our highly trained staff and testing facilities are at your service



ORR-OLIVER

COMPANY LIMITED

ABFORD HOUSE, WILTON ROAD, (VICTORIA), LONDON, S.W.I

VOL. LXXVI No. 194 IO NOVEMBER 1956

The international weekly chemical journal covering every aspect of industrial chemistry and chemical engineering

OVERSEAS AGENTS

Argentina, Inter-Prensa, Florida 229, Buenos Aires • Australia, I. M. Cullen & Co. Pty. Ltd. (2 Howard Street, Perth. Gordon & Gottch (Australas) Let., 262-264 Adelaide Street, Brisbare Queensland. The Grahams Book Com. 1940. Merin Martin Street, Sydney, N. S.W. John Mitton & Go., 164 Pitts Street, Dydney, N. S.W. John Mitton & Go., 164 Pitts Street, Dydney, N. S.W. Jeros Manuel I. L. S.W. J. 100 Burke Street, Sydney, N. S.W. Jeros Manuel I. L. S.W. J. 100 Burke Street, Sydney, N. S.W. Jeros Martin & Gotterens Street, Sydney, N. S.W. Jeros Martin & Gotterens Street, Sydney, N. S.W. J. 17-75 Boulevard Adolphe Max. Postal 2786. Sao Paulo • British. West Indies, Christopher B. Hills, 101-103 Harbour Street, Kingston, Jamaica • Canada, W. H. Smith & Son (Canada) Ltd., 224 Yonge, Street, Toronto • Caylon, The City Stores Ltd., Kandy. The Lake House Bookshop, McCallum Road 10, Colombo • Chile, The E. S. Blair Company, Banders 172-80 Piso-01a 14, Santiago, Chile. • Cyprus, The Union Trading Co., P.O. Box 123, Larnaca • Cacheslowakia, Artia Ltd., 3D Ve Smeckach, Prague II • Demmark, Illustrated News Service, Dahlerupsgade I, Copenhagen V • Egypt, S. S. Bassous, P.O. Box 103, Alaxandria • Finland, Akateeminen Kirjakauppa, Helsinki, Rautatie-kirjakauppa Oy, Helsinki • Fiji, A. A. Shameem & Co., P.O. Box 8, Suva • France, Paul Crampel, 54 Rue Rene Boulanger, Paris X • Germany, Buch und Zeitschriften-Union, Harvestehuder Weg S, Hamburg 13. W. E. Saarbach G.m.b.H., 30, Gertrudenstrasse, Cologne 19 Holland, Dekker en Nordemann's Wetenschappelijke Boekhandel N.V., O.Z. Voorburgal 243, Amsterdam C. Meulenhoff & Co., N.V., 2-4 Beulingstraat, Amsterdam • Holland • Germany, Buch und Zeitschriften-Union, Harvestehuder Weg S, Hamburg 13. W. E. Saarbach G.m.b.H., 30, Gertrudenstrasse, Cologne 19 Holland, Dekker en Nordemann's Wetenschappelijke Boekhandel N.V., O.Z. Voorburgal 243, Amsterdam C. Meulenhoff & Co., N.V., 2-4 Beulingstraat, Amsterdam • Holland • Germanny, Buch und Zeitschriften-Union, Harvestehuder Weg Service, Danyol 25

THE CHEMICAL AGE

NEWS of the WEEK

Free Trade Area	241
British Chemical Plant Orders	242
Note & Comment	243
People in the News	244
Carbonisation & Chemical Plant	245
US Chemical Costs	248
European Free Trade Area	249
South African Developments	250
Styrene Monomer Plant Extends	251
Chemist's Bookshelf	252
Diary Dates	253
Overseas Chemical Expansion	254
All-Electronic Control System	255
Commercial Intelligence	256
Market Reports	256

BOUVERIE HOUSE · FLEET STREET · LONDON · EC4

Editor GEOFFREY F. D. PRATT Telephone: FLEet Street 3212 (26 lines)
Telegrams: Allangas · Fleet · London

Director

N. B. LIVINGSTONE WALLACE

Manager


H. A. WILLMOTT

Midlands Office, Daimler House, Paradise Street, Birmingham Scottish Office, 116 Hope Street, Glasgow C2 (Central 3954/5)

Leeds Office, Martins Bank Chambers, Park Row, Leeds

(Midland 0784/5) (Leeds 22601)

The annual subscription is 52s 6d (\$7.40), single copies 1s 3d (by post 1s 6d). Overseas subscribers may send their subscriptions direct to London, or remit through any of our agents.



EMPILAN MB 303

foam booster and stabiliser

Empilan MB 303 is a new and economic additive for liquid detergents with particular affinities for the popular anionic types. Its presence synergistically boosts detergency and increases fat emulsifying power, thus permitting the formulation of highly concentrated detergent products. The imparting of a pleasant 'soft' feeling to anionic liquid detergent, and a gearing of foaming power to cleaning power, are among other desirable features of this new addition to the comprehensive range of chemicals by Marchon.

MARCHON PRODUCTS LIMITED

AGENTS AND OFFICES IN PRINCIPAL CITIES OF THE WORLD

Head Office: Whitehaven. Telephone: Whitehaven 650 & 797 (11 lines) Telegrams: Chems, Telex, Whitehaven.

London Office: 140 Park Lane, W.1. Telephone: Mayfair 7385 (3 lines) Telegrams: Marchonpro, Telex, London.

VIEWPOINT

Free Trade Area

A GENERATION or so ago nothing stirred political emotions more certainly than 'free trade,' yet the Chancellor's autumnal proposal that Britain should consider supporting the European Customs Union project caused less public rustling than the falling leaves. To the public—even before the Middle East crisis preoccupied thought and headlines—the issue was the concern of politicians, economists and industrialists.

No one need assume that this atmosphere of public disinterest would not suddenly alter if the course taken

began to produce unfavourable results.

The form of association which the Government has in mind would be a partial free trade area, consisting of the customs union of the Brussels group of six powers, the UK and such other OEEC countries as wished to join. The difference between a free trade area and a customs union is that in the latter case there is a common tariff against all other countries, while in the former each country is free to preserve its own tariff against other countries outside. Within such an area, tariffs (except for revenue purposes) would be gradually reduced and ultimately abolished. The period suggested in Government circles is 10 to 15 years.

Considering the UK attitude on the proposed European Customs Union, the Chancellor has pointed out that if Western Europe, including the UK, could develop into a free trading area, this would prove 'a great source of strength'—Britain would have the full advantages of large-scale production. Moreover it would be advantageous for the Commonwealth as a

market and as a source of capital.

Such efforts as have been made to sound opinion in industry have not been very revealing, but during a period when many industrial associations have been considering the views they should express to the Board of Trade, this cautious attitude is understandable. The main impression gathered, however, is that the pros and cons of the proposal are matters of detail rather than of principle, that no one can reasonably say whether it will be a good or bad thing to join in a Customs Union until the terms of membership have been clearly stated. What has so far been said by the Government has been too tentatively defined for reaction from industry to be itself any less tentative.

Tariffs are forms of discrimination, but they are not the only kinds that are used today. A Customs Union of Western European countries would not bring completely free trade if import restrictions by quota systems persisted. Thus, Britain could open to another country one of her commodity markets now mainly supplied by home industry, yet find the quid pro quo expectation

of selling other commodities in their markets barred by quota limitations. Also, there is the problem of currency, both in its exchange values and terms of credit. A subsidised system of long-term credit on export sales—already not unknown in international competition—would be even more influential under free trade conditions. Nor is credit all that can be subsidised. The goods sold by a country can be subsidised, and hitherto it has been possible to protect a home industry against this disguised form of dumping only by placing tariffs on imports. It is right, nationally right and not merely through self-interest, for industry to insist that these unknown risks in a Customs Union shall be clarified before any decisions are made.

An example from the chemical industry of this type of risk is not hard to find. Some 25 or 30 years ago superphosphate was traded in Europe at prices often well below its cost of production, and this led to the closing down of numerous manufacturing units and to the technical atrophy of others. No agreement that is related to tariff rates alone will eliminate these other methods of non-free trading—it could, on the contrary, encourage them in any time of trade recession.

Ideally, a Customs Union between countries requires equal impacts of taxation and labour costs upon the costs of manufacture. No one supposes that these are conditions that can be created. In the price make up of most chemicals, the labour cost is low in comparison with many other goods manufactured here. On the other hand, the effects of high taxation on profits, particularly in discouraging investment and plant expansion, fall severely upon chemical industry.

A qualified approval has been given by the TUC on the desirability of Britain joining a partial free trade area in Europe, providing living standards are safeguarded. The favourable view of the TUC to closer economic integration would appear to be due to the feeling that the country cannot afford to be outside.

Yet there must be set against all these doubts another and quite different argument. Will it not endanger British future trading more if the country stands aloof from the Customs Union project? Is there as much choice as is sometimes supposed? If Britain does not join, a mass market in Western Europe will gradually reduce tariffs for German goods while retaining them upon British goods. The country must export to live. A principal reason for this is that a substantial proportion of the national diet has to be imported, and it is already agreed that food supplies will be outside any Customs Union agreement. Judged against this background, the case for joining the Customs Union is powerful, if not undeniable.

BRITISH CHEMICAL PLANT ORDERS

Overseas Contracts 'Increasing'-BCPMA Chairman

LINKS BETWEEN the chemical and petroleum industries, the latter soon to be expanded by a one-third increase in the refining capacity in this country, have led to petrochemical plant developments, declared Mr. G. N. Hodson, chairman of the British Chemical Plant Manufacturers' Association Council, on 31 October. He was speaking to over 600 members and guests at the Association's annual dinner in London.

Referring to the 'complete chemical contractor' and the growing wealth of experience and know-how, Mr. Hodson said large contracts were now being awarded with increasing frequency by overseas countries to British chemical engineering firms.

Turning to domestic matters, the chairman referred to the BCPMA information service and to visits paid by members of the research committee to various universities in connection with chemical engineering students and studies.

In a reference to the atomic energy programme, Mr. Hodson pointed out that many of the Association's 220 members had done work for the UKAEA and had thus added to their skill and experience in making and fabricating large-scale chemical plant. The AEA demands had been exacting—a challenge which the industry was equipped to meet. 'This is a measure of the experience and skill available in our industry to meet the searching demands of the chemical industry at home and abroad,' added Mr. Hodson.

' Valuable Contribution'

Sir John Cockeroft, director of the UKAE research establishment, who was the principal guest, said members of the Association had made a valuable contribution to the development of atomic energy during the last decade. At the Windscale chemical separation plant, so good was the quality of the basic research, so good the design, and so excellent the quality of the welding, that few troubles had been experienced. The 'impossible' maintenance of active plant had been shown to be possible. 'For this we have to thank the chemists, designers, builders and operators,' remarked Sir John.

The industry had made important contributions to plant for the extraction of uranium from ores, he continued. The industry was far from its peak. In the future, the amount of uranium ore to be processed in the US will rise from three to six million tons a year; annual production of

uranium oxide in the free world will reach 30,000 tons a year. Capital expenditure on plants will be made. Declared Sir John, 'Here is opportunity for the chemical plant manufacturing industry.'

In the field of basic atomic energy materials the demand for super-pure reactor grade graphite grows rapidly with time. Exotic materials such as beryllium, niobium, zirconium are demanded in tens of tons. A decade ago they existed in tens of grams only. Temperatures of 100 million degrees may be necessary for operating plants of the future.

... 'Those mighty pressure vessels surrounding the reactors at Calder Hall—an almost incredible feat of welding and stress relieving ... were thought to be the largest which under all the circumstances could be built. Now the building of much bigger and thicker vessels is envisaged. ..' Mr. G. N. Hodson at the BCPMA dinner.

Only the highest standards sufficed and many of the lessons learnt in building plant for atomic energy, and the processes and technology used, had application in fields outside atomic energy.

On the vital subject of training, Sir John had this to say: 'Your members take a vigorous interest in courses and support the drive for more technicians and technologists. Self-help is certainly the surest way. But more can be done by exploiting reservoirs of talent in secondary modern schools which now contain 80 per cent of the children. I am a great believer in the potential capacity of the young. Too often, however, this is left dormant.'

BP Plan Objections

OBJECTIONS may be raised by the Milford Docks Co. to the British Petroleum Co.'s £5 million scheme for a tanker terminal at Milford Haven.

The Pembrokeshire county planning committee has been informed of this objection, which would be to the Parliamentary Bill which is being promoted to authorise the BP scheme.

A BP spokesman said that 'as the company has not yet itself decided the exact position of its proposed jetty at Milford Haven, it is clearly impossible to say at this time whether it would interfere with other users of the Haven.

Extruded Plastics

Application of Rigid PVC and Nylon Pipes

SUMMING-UP the Symposium on Extruded Rubbers and Plastics, held at the National College of Rubber Technology, London N7, on 30 and 31 October, Dr. H. Barron, the symposium's vice-chairman, said that there had been a superb selection of papers on plastics. He apologised, however, for the limited time given to rubber. Tailor-made extrusion products had been discussed and he thought more would be heard of irradiated polymers.

A new terminology—'reasonable infinity'—had been mentioned. Dr. Barron was sure that this phrase would become a common term as an answer to the question 'How long will this plastic last?' The word superpolythene, now applied to Marlax 50, discussed by J. J. P. Staudinger (British Resin Products), might also be heard more often in the future.

It was evident that the paper by D. J. van Wijk, of the Plastics Research Institute, TNO, Delft, Holland, on the application and testing of rigid p.v.c. and nylon pipes for conveyance of fluids had aroused considerable interest. Such had been the demand for copies of the standard for specifications and test methods for pipes with external diameters up to 40 mm. made of rigid p.v.c. and intended for use as water pipes, which Dr. van Wijk had brought along, that further copies would be run off and forwarded on request as soon as possible.

Atomic Energy Films

DETAILS of 145 films on atomic energy and related subjects are contained in the October 1956 issue of Scientific Film Review. This is the first comprehensive list of its kind. The information is arranged alphabetically by film title and there is a subject index covering the following categories:

Application of radioactive isotopes in agriculture, biology, chemistry, general surveys, handling, industry, metallurgy, meteorology; atomic bomb and civil defence; equipment and apparatus; general surveys; moral, political and religious problems; natural resources; nuclear reactors; occupational safety, progress reports; research centres and atomic energy plants; theoretical aspects.

Single copies of this issue are available direct from the Scientific Film Association, 164 Shaftesbury Avenue, London WC2, price 3s 6d.

NOTE & COMMENT

SUEZ AND INDUSTRY

WHEN THIS NOTE was written the Suez Canal was closed. When the Canal is reopened, considerable repairs and clearance will be required. Yet, in the present situation, oil is a vital commodity. Three-quarters of Europe's total requirements are at present met by Middle East supplies. At the current rate of consumption this is equivalent to 100 million tons a year of crude and refined products. Of this total, 65 million tons a year have been passing through the Canal. Indeed, so far this year the figure is estimated at 75 million tons. The amount of oil reaching the UK through Suez is 20,543,000 tons (56 per cent of total imports), some 12,148,000 tons (47 per cent) goes to France, 7,248,000 tons (63 per cent) to Holland and 8,630 tons (15 per cent) to the US.

Present stocks of oil in UK are at their highest level, having been built up since July in anticipation of the possibility of difficulties associated with the Canal. But these stocks only represent six to eight weeks' supply (5 million tons). The greater part of the stocks probably consist of crude oil in the possession of the oil companies. Further supplies should be reaching these shores in 10 to 15 days' time when tankers already en route should arrive.

Tankers are being diverted to the Cape route, but this will increase considerably the delivery time and the cost. In fact, it is estimated that Europe's total oil supplies can be expected to fall by between one-sixth and one-quarter unless more oil is imported from other

Unless the Canal is reopened to traffic in the near future, it seems possible that rationing of oil and petrol in the UK may have to be imposed.

POSSIBILITY OF SABOTAGE

SABOTAGE of pipelines and pumping stations in the Middle East has been a possibility from the beginning. On Monday it was reported that the flow of oil from Iraq (33.9 million metric tons in 1955) to the Mediterranean had stopped completely with the blowing-up of the Iraq Petroleum Co.'s three pipelines.

Another pipeline said to have been sabotaged is that of the Qatar Petroleum Co. which runs to the Persian Gulf and carries 5½ million tons of oil annually.

No move to supply Western Hemisphere oil to Europe has yet been made by the US Government, but there have been reports that overseas oil buyers are trying to obtain crude oil from the US and Venezuela. US sources are believed to be sufficient to meet the emergency demand for a week or two, but if the pressure were still on by the end of November shortages would begin to develop.

Largest user of fuel oil in Britain is industry (3,830,000 metric tons). Transport takes a total of 8,395,000 metric tons of all varieties of oil, domestic and commercial take 1,428,000 tons of all types; industry's total excluding fuel oil is 1,078,000 metric tons.

Apart from oil, other commodities which have been transported through Suez include rubber, copper, tin, lead, zinc, jute, etc. Therefore, the importance of the Suez Canal to Britain's economy cannot be overemphasised. The situation is too serious to admit of political manoeuvres.

POLYMERISATION RESEARCH

NEW VIEWS on paths of reaction in low pressure polymerisation of polythene were recently reported at the American Chemical Society Division of Polymer Chemistry's Symposium on new olefin polymers at Atlantic City. (Chem. & Eng. News, 8 October 1956, 4881.) Thus Standard Oil of Indiana are employing nickel-charcoal and molybdena-alumina catalysts which give polythene at low pressures. In the oxidised state, these catalysts are said to have very little activity, but heating in the presence of hydrogen activates both by partial reduction.

Nickel-charcoal polymers are stated to be softer, more flexible and more soluble than those produced using a molybdena-alumina catalyst. Other interesting properties are that molybdena-alumina polymers have greater strength, greater density and crystallinity and double bonds are about 70 per cent internal and 30 per cent external.

Activation of the catalyst in a manner similar to hydrogen, but at lower temperatures, is possible using promoters. Thus, sodium, calcium hydride, and lithium aluminium hydride have been found to activate molybdena-aluminium catalysts. Such promoters reduce and activate spent catalysts, scavenge catalyst poisons present and enter directly into the catalytic process. Ethylene polymerisation over a molybdena-alumina catalyst with calcium hydride has been found to be 30 times that when no promoter was used.

Other research investigations have shown that organometallic compounds such as monovalent butyllithium and titanium catalysts are involved in important mechanisms of initiation, growth and termination of ethylene polymerisation.

Growth reaction mechanism for polymerisation in which the metallic ion is bound to the surface has been proposed. An ion-radical forms by reaction with adsorbed olefin.

People in the NEWS

- Managing director of Griffin & George Ltd, laboratory furnishers, and chairman of the British Laboratory Ware Association, Mr. Norman McKinnon Wood, sailed from Liverpool recently on a visit to the US. He will call on the company's agents and see customers to ascertain the US users' particular needs in laboratory equipment.
- Remington Rand Ltd. has formed an electronics division because of the immense potential in the field of electronic office equipment. Heading the division is Mr. C. W. ELLIOTT as national sales manager.
- At the autumn convocation of the Textile Institute in Manchester on 26 October, the Warner Memorial Medal (awarded in recognition of outstanding work in textile science and technology, the results of which have been published) was presented to DR. J. M. PRESTON (Aintree). DR. F. C. Toy (Wilmslow) also received the Institute Medal for distinguished services to the textile industry in general and to the Institute in particular.
- Formerly London area sales manager of The National Gas & Oil Engine Co. Ltd., MR. W. L. BECKETT. has been appointed London manager of the company and a director of its subsidiary, National Oil Engines (Export) Ltd. In both positions he succeeds MR. F. D. LANGLEY, who has retired after 34 years' service with the parent company.
- Joint winners of the 1956 Nobel prize for chemistry are Professor Sir Cyril. Hinshelwood, president of the Royal Society and Dr. Lee's Prefessor of Chemistry at Oxford, and Professor Nikolal Semenov of Moscow. They win the prize for their researches into the mechanism of chemical reactions and will share prize money of

more than £14,000. Sir Cyril, who is a past president of the Chemical Society, has said that he and Professor Semenov met in Moscow in 1945. They had exchanged papers and views and worked along related lines; although not on quite the same lines. He hopes to go to Stockholm to receive the prize. Professor Semenov is the first Soviet citizen to receive a Nobel prize.

- Native of Porthcawl, South Wales, MR. GEOFFREY SIMS-DAVIES (43) has been appointed equipment manager of British Oxygen Gases Ltd. He joined British Oxygen in 1938 as an assistant engineer, and became chief engineer for British Industrial Gases in 1940. Latterly he has been BOC district engineer for Lancashire. MR. ROBERT FANNON, formerly superintendent of the process development section British Oxygen, Cricklewood, becomes assistant to Mr. Sims-Davies.
- DR. W. M. CUMMING, O.B.E., D.Sc., F.R.I.C., F.Inst.Pet., M.I.Chem.E., F.R.S.E., formerly of The British Dyestuffs Corporation, Huddersfield, and later professor of technical chemistry and director of the School of Chemistry in what is now The Royal College of Science and Technology, Glasgow, has retired from his post as technical director to The British Dyewood Co. Ltd. and has set up as a technical consultant. All communications should be addressed to 6 Maryville Avenue, Giffnock, Glasgow.
- Professor R. D. Haworth, F.R.S., professor of chemistry at Sheffield University, has been awarded the Davy Medal by the president and council of the Royal Society in recognition of his distinguished contributions to the chemistry of natural products, particularly those containing heterocyclic systems.
- Chairman of the newly formed Dyers of Man-made Fibre Fabrics Federation Ltd. is Mr. James Ewing of the BDA and the secretary is Mr. John Ainsworth. Members of the council include: Mr. P. F. Crosland, Mr. W. Crossley, Mr. D. Haroun, Mr. F. Cusack, Mr. J. Ruddy, Mr. J. A. Stott, Mr. S. Foster, Mr. E. P. Hanrahan, Mr. G. H. Heap and Mr. J. Blakeley.
- MR. JAMES B. LONGMUIR, who has represented Megator Pumps & Compressors Ltd. in Scotland for the past six years, has been appointed to the newly created post of Scottish regional manager.

Atomic Lubrication

Molybdenum Disulphide Used at Calder Hall

LUBRICATION of the 60 control mechanisms at Calder Hall atomic power station is carried out by the use of molybdenum disulphide manufactured by Rocol Ltd. of Rocol House, Swillington, Leeds, Yorkshire. Ordinary lubricants are rendered useless by nuclear radiation and by the atmosphere of dry carbon dioxide. Water vapour is required for graphite lubrication.

Tests were carried out on many types of solid lubricants and those based on molybdenum disulphide manufactured by Rocol were found to be the most satisfactory. Rocol developed a varnish known as Molytox which produces a molybdenum dioxide film.

Molytox is also claimed to provide protection against corrosion by carbon dioxide, heat and humidity.

Ethylene Glycol Plant

IMPERIAL Chemical Industries Ltd. is building a second ethylene glycol plant, together with increased ethylene oxide capacity, at its Wilton works in North Yorkshire. It will come into production early in 1959 at the same time as the third olefine plant, from which it will draw its ethylene. The combined capacity of the two ethylene glycol plants will be 16,000 tons a year. The principal uses of ethylene glycol are for Terylene fibre, motor car anti-freeze, and explosives.

New Resin Development

GOOD compatibility characteristics are claimed for Scopol 41HM/70, a new resin made by Styrene Co-polymers Ltd. Scopol 41HM/70 is a long oil alkyd copolymerised with vinyl toluene. It is said to combine resistance to conditions promoting bloom formation with good drying properties under adverse weather conditions. It is recommended for use in decorative finishes.

Protective Duties

AN APPLICATION for increased protective duties on antimony metal, in any form; antimony oxides and mixtures containing not less than 85 per cent by weight of antimony oxides expressed as antimony trioxide; and, alloys of metal, in any form, containing not less than 85 per cent by weight of antimony, is being considered by the Board of Trade.

Carbonisation & Chemical Plant

NCB £10m. PROJECT AT WINGERWORTH

HE National Coal Board's £10 million Avenue Carbonisation and Chemical Plant at Wingerworth, near Chesterfield, said to be the most modern and completely integrated of its kind in Britain, was opened by the Minister of Fuel and Power, Mr. Aubrey Jones, on Tuesday 30 October. The site is three quarters of a mile long and covers 188 acres. There are two and three quarter miles of roads and 13 miles of rail track. Some 760 men were employed on construction, which was completed in four years. The total staff and men employed to run the plant is 475.

The plant embodies a basic coking unit, consisting of two batteries, each of 53 Woodall-Duckham Becker Combination Underjet type ovens, together with primary and secondary by-product plants. The batteries are built in line with the coal storage bunker between them and with two stacks centrally located on the west

View of the Avenue carbonisation and chemical plant. Photograph by courtesy of Woodall-Duckham Construction Co. Ltd. side of the bunker. One of the batteries has been in operation for some months; the second battery went into operation after the official opening. Each oven is 41 ft. 1½ in. long between the doors, 13 ft. high with an average width of 16 in. and a capacity of 657 cu. ft. They are arranged for heating either by coke oven gas when the underjet system is employed or by producer gas generated in the producer gas plant.

There are four charging holes per oven, each of 18 in. diameter, and two gas take-offs per oven. The oven chimneys are 250 ft. high with an internal diameter of 9 ft. The service bunker has a coal capacity of 4,000 tons. Special self-sealing doors of a new design developed by the Koppers Co. of Pittsburgh, US, are fitted to the ovens. They are in operation for the first time in Britain.

When the plant is in full production it will carbonise 2,175 tons of coal containing 8 per cent moisture a day, to produce 1,400 tons of coke and 27 million cu. ft. of gas daily. Layout has been designed to allow future capacity to be doubled by the provision of further buildings and

equipment without disturbing the present layout.

Much of the gas produced is used to fire the oven heating flues, but some 14 million cu. ft. a day will be fed into the public gas supply.


Chemical plant, which includes both primary and secondary by-product units, handles the by-products not only of Avenue but also of other coke ovens in the East Midlands Division. It can deal with the by-products from 4,500 tons of coal a day, and the output includes sulphuric acid, sulphate of ammonia, benzole, pure toluene, pure xylene, pitch, pitch creosote fuel, high grade naphthalene, carbolic and cresylic acids, pyridine and anthracene.

Equipment included in the primary by-product section is designed for the cooling and washing of the gas for the recovery of tar and ammonia liquor, the removal of naphthalene and the dilution and boosting of the purified gas available for distribution.

Gas from the downcomers passes in two separate streams to the primary coolers, exhausters and tar extractors

There are five primary coolers of the Whessoe multipass vertical water





The benzole scrubbers, secondary naphthalene washers and ammonia washers. Photograph by courtesy of Woodall-Duckham Construction Co. Ltd.

tube type arranged to work in parallel with two coolers for each gas stream and the fifth as a common standby. The coolers each have six passes and a water cooling surface of 16,500 sq. ft. From the primary coolers the gas is passed by the exhausters to the electro-detarrers.

The three exhausters are BTH turbo-exhausters of axial inlet radial flow type. There is one exhauster for each gas stream with the third as a common standby and each is capable of passing all the gas produced by one battery and of delivering it against a back pressure of 21 p.s.i. although they normally operate between 1 and 1 p.s.i.

Each exhauster is direct-coupled to a steam turbine operating with steam at 120 p.s.i. and exhausting against a back pressure of 15 p.s.i. An Askania regulator controls the hydraulically operated steam throttle valves and maintains a constant suction on the gas inlet.

Electro-detarrers

There are four Whessoe W-D electro-detarrers of 8 ft. dia. These are of the vertical tube suspended wire electrode type. Normally two detarrers are in operation on each gas stream but any three units are capable of handling between them the total gas of both streams. Alternatively, one detarrer can be taken off either stream with only a slight reduction of tar extraction efficiency on that stream.

From the electro-detarrers the gas passes to a range of primary naphthalene washers and, after re-cooling in the secondary condensers, to the ammonia washers. The four primary naphthalene washers are of W. C. Holmes design and there are two working in series in each gas stream. Each can be by-passed. Each washer has four washing chambers with timber and reed filling. The oil used as the washing medium is anthracene oil from the tar plant and it is treated in a W. C. Holmes oil regeneration plant.

The gas is then cooled in two Whessoe multipass vertical water tube type condensers, one in each gas stream. Each condenser has six passes and a water cooling surface of 13,000 sq. ft.

Ammonia Washers

Six W. C. Holmes ammonia washers are arranged so that three operate in series in each gas stream. Any unit can be by-passed as the remaining units are capable of dealing with the total gas load. Each washer has four washing chambers and is identical in design and size with the primary naphthalene washers.

Washing medium is weak 'fixed' liquor bled from the flushing liquor main and/or condensate from the crude benzole separators and, to remove the final traces of ammonia, a limited quantity of soft water. Special coolers reduce the temperature of these liquids before use. The strong ammonia liquor leaving the washers gravitates to the strong liquor sump.

Gas leaving the ammonia washers passes through a vertical down flow type water separator to remove

NCB Plant

entrained moisture and on through three benzole scrubbers,, which are 106 ft. high and 13 ft. 6 in. dia., to the secondary naphthalene washers through which it passes in two streams.

The four W. C. Holmes secondary naphthalene washers are identical with the primary naphthalene washers and two are arranged to operate in series in each gas stream.

The gas purification plant, designed and constructed by Newton Chambers & Co. Ltd., is of the tower type and can purify 26 million cu. ft. of gas per day. The whole plant comprises two sets of towers operating in parallel, each set being capable of purifying half the total throughout. The purification process is based on the normal reaction between hydrogen sulphide and the contact mixture of hydrated oxide of iron, and hydrogen sulphide is removed from the gas down to the statutory limits prescribed by the Gas Regulation Acts.

Gas purification plant comprises four Waller gas compressors, each of which is capable of compressing 6,000,000 cu. ft of gas per day measured at 60°F and 30 in. Hg and of delivering it at a pressure not exceeding 25 p.s.i. Two are steam driven and two electrically driven and each is capable of boosting six million cu. ft. per day at a maximum pressure of 25 p.s.i.

There are two Holmes Connersville meters of the positive displacement type, each with a normal capacity of 10,800,000 cu. ft. per day which, for emergency use, can be increased to 16,200,000 cu. ft. per day. The meters are arranged to operate together in parallel.

The purified gas holder is a Newton Chambers two lift spirally guided holder with a storage capacity of 500,000 cu. ft. It is of welded construction and the tank is 108 ft. 6 in. in diameter. When fully inflated the holder throws a pressure of 9 in. w.g.

Kachkaroff Acid Plant

Kachkaroff sulphuric acid plant was installed by Simon-Carves Ltd., the design being provided under licence by The Chemical Plant & Sulphur Extraction Co., London. The process works on the principle of the intensive tower system. The only other similar plant in this country is at the South Eastern Gas Board works at Phoenix Wharf. At Wingerworth, Flixborough rotary burners are installed with the specific object of so treating the spent oxide that the result-

Wingerworth

ing cinder, as recovered, when mixed with peat and sawdust, is suitable for re-charging to the oxide bones for H₂S removal, without further addition of revivifying material.

There are two rotary burners included in the plant for burning spent oxide with a normal sulphur content varying between 46 per cent and 48 per cent. Each burner comprises an inner and outer shell, the outer being constructed of mild steel and lined with firebrick and provided with oxide lifting apparatus. The inner shell or tube is constructed in heat resisting steel to withstand the temperature obtaining within the burner. After ignition of the spent oxide, the oxide and cinder passes to the discharge point and the gases produced return to the feed end where they are conveyed to the gas ducts and dust removal system before being boosted for entry into the Kachkaroff acid plant.

Furnace gases containing five to six per cent SO, enter the acid section of the plant at the concentration tower and pass in parallel through the denitration tower, which is divided vertically into two sections, both towers operating under slight pressure. After cooling in the atmospheric cooler, the gases are drawn through the four reaction towers by means of a fan and finally escape to the atmosphere via the filter tower. All gas flows, other than in the reaction towers, are in counter current to acid. Gas therefore passes through the concentration tower, denitration tower, reaction towers, and filter tower in that order and acid circulations are maintained over each tower by means of circulating pump systems associated with acid cooling plant.

Sequence of the process is (a) receipt of the spent oxide from the tower puri-

fiers where sulphur as sulphuretted hydrogen has been recovered from the coke oven gas, (b) combustion of the sulphur to sulphur dioxide, (c) conversion of the sulphurdioxide to sulphur trioxide and the formation of sulphuric acid which is used to make ammonium sulphate from the ammonia also recovered from the coke oven gas. The cinder produced is mechanically blended with peat and sawdust and the mixture is returned to the oxide towers, thereby completing the cycle. The plant is capable of producing 65 tons per day of 77 per cent acid.

The Royston ammonium sulphate plant is capable of producing 35 tons per day. It consists of two Woodall-Duckham stills, one working and one as a stand-by, together with Limbux liming equipment; two saturators and auxiliary equipment, one working and one as stand-by; flash drying equipment for drying and neutralising; and automatic bagging and storage for 1,500 tons bagged sulphate.

Effluent Treatment

Effluent treatment plant was designed by The Permutit Co. Ltd. on the basis of the Corby process, and developed by co-operative research with the Woodall-Duckham Construction Co. Ltd. and Stewarts & Lloyds Ltd.

Its purpose is to purify the noxious effluent from the sulphate plant so that the liquor can be discharged safely into the river. The plant employs a new process of dealing with the noxious liquor and is the result of many years of research and development.

The pusher side of the north battery at the new Avenue carbonisation and chemical plant (left) with the coke side of the batteries (north battery in operation, south battery with temporary heating-up pipe in position) to the right. Photographs by courtesy of Woodall-Duckham Construction Co. Ltd. The plant was designed to purify up to 185,000 gallons of liquor daily. It removes thiocyanates and thiosufphates and concentrates them into a volume of 1.1 per cent of the inlet liquor for easy disposal. In addition, the monohydric phenols are recovered and passed to another section of the coke works for final purification.

Care has been taken to ensure that the maximum volume of ammonia, hydrochloric acid and benzole are recovered and distilled, where necessary, for further use, thus reducing the make up requirements.


Purification Stages

Purification is carried out in the following five stages; Settling and cooling; filtering and acidification; removal of thiosulphates and thiocyanates by ion exchange; concentration of the reject liquor containing thiosulphates and thiocyanates; removal of phenols and higher tar acids by activated carbon absorption.

The hot untreated effluent passes first to one of two 62,000 gallon concrete sedimentation tanks. The settled effluent is then pumped from the sedimentation tanks through a rack cooler to a cooled effluent sump.

Liquor is pumped from the cooled effluent sump by the main feed pump and passes through a battery of four sand filters. It is then dosed with hydrochloric acid to lower the pH to a suitable level for ion exchange treatment.

Thiosulphates and thiocyanates in the liquor are removed by a battery of three ion exchange units containing De-Acidite ion exchange material. When the capacity of this material is exhausted the accumulated inorganic salts are removed by flushing with ammonia solution. The free ammonia in this reject liquor is recovered by distillation in a separate ammonia distillation plant. The reject liquor from this ammonia distillation plant is concentrated to a small volume in a submerged flame concentrator which





NCB Wingerworth

reduces the bulk to about one per cent of the effluent treated.

The De-Acidite treated liquor is collected in a storage tank and pumped to a battery of carbon filters which remove the monohydric phenols and higher tar acids.

When the carbon has become saturated the phenols and tar acids are removed by treatment with benzole. The majority of this benzole is recovered in a separate benzole distillation plant. The reject liquor from this plant consisting of phenols and tar acids and a small proportion of benzole is worked up in a separate part of the Avenue plant. The effluent from the carbon units is then treated with lime and discharged as a colourless innocuous solution into the works drain system.

Benzole Rectification

A Woodall-Duckham benzole rectification plant of 20,000 gallons per day capacity has been installed to produce pure products for the chemical industry. In this section the CS, free one-run benzole from the recovery plant and imported CS, free benzole are washed and treated in continuous and batch rectification stills for the production of motor spirit, toluole and all grades of benzole fractions including pure products. The equipment includes benzole washers, continuous benzole and toluole columns and batch stills for pure benzole, toluole and xylole production.

For the production of motor spirit or benzole fraction the product from the once-run column of the recovery plant or the imported product is washed with acid and soda in the benzole washers.

A Chemical Engineering Wiltons Ltd. tar plant, of 200 tons per day capacity, is designed for an eventual daily capacity of 400 tons of crude tar. The plant comprises the following unit processes: Wilton tar distillation unit; tar acids extraction unit; tar bases extraction unit; naphthalene unit; anthracene extraction unit; blending unit; pitch production; and storage.

In the Wilton tar distillation unit the crude tar is fractionated to pitch and the following oils: Benzole, solvent naphtha, carbolic oil, naphthalene oil, creosote, anthracene oil. The unit is operated continuously and incorporates a radiant type pipe still. It is flexible in operation both in regard to throughout and the hardness of pitch.

The tar acids extraction unit extracts tar acids continuously from the carbolic and naphthalene oils produced in the distillation unit. The extraction is achieved by reaction with caustic soda prepared in the causticising plant. The cresylate solution produced is de-oiled and contacted with CO₂ to release the tar acids. The sodium carbonate solution is returned to the causticising plant for regeneration. The steam boiler situated on the site is primarily intended for production of CO₂ the steam raised being consumed within the works.

To recover tar bases (principally pyridine) a number of the oils from the distillation unit are washed with sulphuric acid in the tar bases extraction unit. The sulphates produced are then reacted with ammonia gas to release the tar bases. These bases are subsequently dried by washing with caustic soda.

Naphthalene oil from the distillation unit is treated to produce saleable naphthalene either in the form of liquid or flake. This naphthalene is mainly used in the production of phthalic anhydride. The naphthalene oil is fed to static crystallisers, allowed to cool and crystallise and the oil is drained off. The crystals are then washed with methanol solution to remove the maximum amount of the remaining oils. The methanol solution is redistilled for further use.

Anthracene oil from the distillation unit is first allowed to crystallise and the oil drained off. The crystal magma is then centrifuged to produce an anthracene paste which is fed to a hopper for subsequent bagging. The blending unit, which consists primarily of mixing vessels, is used for the production of pitch creosote blends, road tars, or fuel oils, to various specifications.

Part of the pitch is used for production of pitch creosote blends or road tars. Subject, however, to market requirements a proportion of the pitch is stored in solid form in open bays. Facilities are available for increasing the hardness of the pitch produced on the distillation unit. This harder pitch has a number of applications among which are electrodes, coal blending and pulverised fuel.

The whole plant at Wingerworth is serviced with power and steam. The steam raising plant consists of three breeze-fired water tube boilers of the Babcock CTM type, each generating 60,000 lb. of steam per hour at 475 p.s.i. and 640°F superheat.

Ceylon's Salt Harvest

THIS YEAR, 80,000 tons of salt have been collected, the greatest-ever salt harvest, while a further 20,000 tons are expected to be collected before the end of the year. Ceylon's annual consumption is approximately 55,000 tons.

Information Guide

Investment and Operating Costs of US Chemical Industry

A COMPREHENSIVE guide to recently published information on investment and operating costs in the petroleum and chemical industries of the United States was released recently by the Bureau of Mines, Department of the Interior.

Intended to aid plant managers and others who purchase equipment and plan operations, the volume contains abstracts of more than 600 articles and technical reports published in the US between July 1952 and June 1954. It supplements two earlier bibliographies on the same subject.

Wide Range of Topics

Topics covered in the new publication range from cost comparison studies for various types of chemicaland petroleum-processing equipment to the chemical engineering aspects of nuclear power. Many of the references are to articles dealing with some phase of the petrochemical industry, reflecting the rapid expansion in this field during recent years.

A copy of information circular 7751, Bibliography of Investment and Operating Costs for Chemical and Petroleum Plants, Supplement 2, July 1952-June 1954 can be obtained from the Bureau of Mines, Publications-Distribution Section, 4800 Forbes Street, Pittsburgh 13, Pa.

Polyol Plant Construction

TO MEET the increasing demand for trimethylolpropane in the rapidly growing polyurethane plastics and coatings field, Celanese Corp. of America has started construction of a new polyol production unit at its Chemcel Plant in Bishop, Texas.

Mr. R. W. KixMiller, vice-president and general manager of Celanese chemical division, in announcing construction of the new facility, reports that it will use special aldoling processes developed by Celanese and will greatly expand capacity for polyol and aldol production which began a year ago with the start-up of a semi-works unit.

The new commercial unit is expected to be completed and producing by the last quarter of 1957. In addition to providing trimethylolpropane and other intermediates for polyurethane synthesis, it will produce a range of other products that will serve end uses in alkyd resins, high quality brake fluids and other expanding industrial fields.

EUROPEAN FREE TRADE AREA

FBI Member Firms' Views Sent to BoT

VIEWS of FBI member firms and trade associations on the question of whether Britain should or should not enter into negotiations with the six Messina countries with a view to participating in a European free trade area were set out in a report submitted to the President of the Board of Trade by the Federation on 1 November.

The Federation, which prepared the report at the request of the President of the Board of Trade, held two meetings of its grand council. The 10 regional councils also met, and the opinions of 287 trade associations in the FBI's membership, which between them cover some 20,000 individual firms, were invited. The Federation also gave an opportunity to any of its 7,400 individual members to express opinions, unless they were satisfied that their views would be covered through one or more of the trade associations.

The 10 regional councils of the FBI each consist of some 30 leading

industrialists drawn from varied firms and cover geographically the whole of England, Scotland and Wales. Each has discussed this problem at length, special meetings having been called for that purpose where necessary. With one exception (the North Midlands) the view was formed that the UK could not afford not to negotiate with a view to reaching acceptable terms for joining a partial Free Trade Area, subject to various conditions. These views, however, were not representative but personal to the men concerned.

Many of the 287 member trade associations have not felt it appropriate to express views on this subject. In many cases trade associations have not been unanimous. The report points out that 'both on these grounds, and also because of the widely differing economic importance of the various industries, it would be quite wrong to express the weight of opinions by merely counting heads.'

ITALIAN CHEMICAL TRADE

Imports Rising More Rapidly Than Exports

ITALIAN imports of chemicals have been increasing more rapidly than exports, according to data released by the National Association of the Chemical Industry in Italy (Istat).

Most anxiety is being felt in the group described as 'various products of the chemical industry,' which consists largely of complex products manufactured in many cases by small or medium size companies which do not have the resources to stand up to keen foreign competition. In the first six months of the current year the value of imports was 14,397 million lire, against 9,480 million lire in the corresponding period of 1955.

Grave Considerations

Our Italian correspondent says that grave considerations are suggested by the data given by Istat. In all branches of the chemical industry, particularly in the principal ones, he says, foreign competition is increasing and shows vigour and aggressiveness both in Italy and abroad, while, with the exception of some categories, the national industry is declining.

Among reasons suggested for this decline are the want of an economic policy consistent with the aims of the Vanoni plan which presupposes for the chemical sector an increase of ex-

ports more than proportional to that of imports, the continual rise in the cost of production, obstacles that hinder new investments, and political interference.

An analysis of the data supplied by Istat shows that in 1955 imports of chemical products increased by 21.9 per cent against a 17.7 per cent increase in exports. In the first six months of this year the figures were 25.3 per cent against 8.1 per cent.

Delegation Returns

THE THREE British plastics manufacturers (Mr. Herbert Bridge, British Moulded Plastics Ltd., Mr. Jack Lesser, Crystalate Ltd., and Mr. R. Sternberg, Sterling Moulded Materials Ltd.) who have been visiting Russia as guests of the USSR Government (see The Chemical Age, 3 Nov., p. 211) have now returned.

They are preparing a full report on their visit, the result of which has been to convince them that a great increase of trade from this country to Russia in plastics raw materials, finished articles, tools and plant is possible. A return visit of a Russian plastics delegation is expected here some time this month.

Protective Suit

Terylene Coated with Geon PVC

A SPECIAL light-weight protective suit of Terylene coated with Geon p.v.c. weighing only 3 lb. (approx) has recently been developed by the RFD Company Ltd., 35/9 Maddox Street, London W1, for rocket research workers. It is designed to give protection against high test peroxide (90 per cent hydrogen peroxide) used as jet and rocket motor propellent. In addition to withstanding attack by hydrogen peroxide, Geon p.v.c. is not harmed by repeated flexing and permanent protection over long periods of service is provided. Personnel on the Rocket Test Beds of the de Havilland Engine Company and Armstrong Siddeley Motors Ltd. are already using the suit.



Protective suits in use on the rocket test beds of the de Havilland Aircraft

Expansion Plans

PLANS for the rebuilding and modernising of Joseph Crosfield's soap and chemical factory at Warrington were announced recently. An eight-year programme costing £5 million is envisaged. It will be financed by the parent company, Unilever Ltd. According to Dr. J. E. Taylor, chairman of Crosfield's, it will take two years for the plan to start.

The present factory buildings lie on both sides of the Mersey. The ultimate intention is to concentrate production on the Lancashire side to avoid the movement of men and materials across to the Cheshire side. To carry out this concentration it will be necessary to build upwards.

Flexicote Developed

Non-Inflammable Asbestos Emulsion Coating

DEVELOPMENT of a new type of asbestos emulsion coating, of interest to companies with a corrosion problem, is announced by Solvolene Lubricants Ltd., Reginald Square, London SE8. Known as Flexikote, the new material is non-inflammable and it is claimed that it can be applied to surfaces such as boiler chimneys that remain at temperatures above 200°F.

Long Life Claimed

Tests have shown that Flexikote has a long life and retains its flexibility and plasticity even when the surface is subjected to continuous vibration or flexing. When Flexikote has been applied, either by brush or low pressure spray, on to any type of surface, it will be found that the coating, while dry to handle after 24 hours, remains slightly tacky indefinitely; it never completely dries out or hardens or flakes, claim the makers, and it is unaffected by fresh water, brine, or sun.

Very little preparation of the surface is necessary before applying Flexikote. Wire-brushing to remove loose rust is normally adequate for iron or steel.

As well as its applications as a corrosion preventative the makers claim that Flexikote can be used as a water-proof sealing compound for brickwork and woodwork.

Coverage obtained from this material works out at about 70 sq. ft. from one gallon, and the cost is said to be less than that of paint.

Tubing and Bungs

BRITISH STANDARD for rubber tubing and bungs for laboratory use (BS 2775:1956) was prepared primarily to reduce the variety of sizes of rubber tubing at present being used. Only metric sizes have been standardised and three thicknesses of tubing are provided for: normal wall tubing, medium wall tubing and thick wall tubing. Two sizes of analytical tubing are provided for. The tube with the smaller bore is to be made of either natural or synthetic rubber; that with the larger bore is to be made of natural rubber. Physical requirements of rubber bungs for laboratory use are specified. It was found impracticable to standardise the sizes of bungs owing to the great variety of sizes in current production.

Copies of this Standard are available from the British Standards Institution, 2 Park Street, London W1.

NEWS FROM SOUTH AFRICA

United Chemicals Detergent Factory

ONE OF South Africa's most hushhush mines is the monazite mine of Steenkampkraal, situated about 54 miles north of Van Rhynsdorp in the north-west Cape. This mine, which has been producing monazite since August 1953, is under the control of the Atomic Energy Board and the product, after preliminary concentration, is sent to America. Water, of which the mine requires 30,000 gallons a day, has to be brought from Klawar, 65 miles away, in four tank lorries. These lorries are also used for transporting the monazite.

United Chemicals & Industrials Ltd. are now operating at a new factory with a floor area of nearly 20,000 sq. ft. at 41 Williams Road, Durban. The new factory has been carefully designed to facilitate the various manufacturing processes involved in the production of the detergents and other chemicals made by the company. Included in the new range of chemical products are liquid and powder detergents for cleaning greasy workshop floors and removing oil from dirty surfaces, and the detergents needed for various types of industrial cleaning and also detergents for home use. Wood preservatives and chemicals for the building industry are also being

Hickman & Kleber (Pty.) Ltd., 271 Umbilo Road, Durban, are manufacturing for industries and laboratories in South Africa a wide variety of special chemicals and allied compounds that are not easy to import because they deteriorate rapidly when stored for any time. They also supply at short notice chemicals which manufacturers might not consider it desirable to keep in stock in quantity. The local firm insists that these manufactures are competing in both quality and price with imports and that it can cope with the most urgent orders at very short notice. It is also possible for manufacturers in South Africa to take their special problems to them for solution, says the company.

Midas Chemicals (Pty.) Ltd., 22 Andries Street, Troyeville, Johannesburg, report that it is now manufacturing nearly 50 industrial adhesives, and in addition is producing various other adhesives to the specifications of customers. This has demanded the provision of large research laboratories. Among the adhesives made by this firm is one for the repair of jute bags. It is also making a variety of release agents for metal, rubber and allied industries, some of these release agents being of the high temperature mould type.

PROVIDING SMOKELESS FUEL

Coal Largest Source of Pollution

TASKS facing the National Coal Board in providing smokeless fuel were referred to by Dr. W. Idris Jones, the Board's director-general of research, at the recent conference of the National Smoke Abatement Society held in Southport. He said that to meet the recommendations of the Beaver committee the NCB would have to increase production of manufactured smokeless fuels. This would call for a vigorous development programme to translate the results of research work into commercial production.

Dr. P. J. Lawthern, director of the Medical Research Council group for research on atmospheric pollution, told the conference that burning coal was the largest source of air pollution. He said there was absolutely no evidence to justify the allegation that diesel engine fumes were responsible for the rise in incidence of lung cancer.

Regulations prescribing authorised fuels to be used in areas of smoke control are being prepared, Mr. Enoch Powell, Parliamentary Secretary, Ministry of Housing and Local Government, told the conference. He said the Clean Air Council would be appointed shortly. The Minister would be chairman and members would be drawn from industry, local authorities and fuel producers. It would be a consultative body.

Coke Ovens Lit

A BATTERY of 150 coke ovens, the largest in Britain, has been lit at the South Bank-on-Tees works of Dorman Long & Co. (Steel) Ltd., and when in full operation will carbonise 25,000 tons of coal a week, producing 15,000 tons of coke. The ovens, which have been built by Simon-Carves Ltd., Stockport, are at present being dried out, and it will be some weeks yet before actual production commences.

Styrene Monomer Plant Extends

FORTH CHEMICALS AT GRANGEMOUTH

N THE DAY this issue of THE CHEMICAL AGE went to press (Wednesday, 7 November) the extensions to the plant of Forth Chemicals Ltd., at Grangemouth in Scotland, were inaugurated in the presence of Sir Miles Thomas, chairman of the company, and directors and senior executives of the three companies jointly associated in Forth Chemicals—Monsanto, BP and Distillers.

Speaking at the inaugural ceremony, Mr. J. M. Pattinson, a director of Forth Chemicals Ltd., said 'the large-scale manufacture in this country of petroleum chemicals has come to stay. There can be no reason for the country continuing to import these when the raw material, refined petroleum, is now available in such large quantities from the refineries which have been built here since the war.'

At Grangemouth the new distillation area incorporates some of the biggest columns ever manufactured for the British chemical industry. The largest is 140 ft. high (THE CHEMICAL AGE, 30 June). The new units are more than double the capacity of those originally commissioned in April 1953 and have increased the

total annual capacity of the plant to over 30,000 tons. They embody all that has been learned from the initial operations and incorporate the latest ideas in instrumentation.

Forth Chemicals manufactures styrene monomer which is increasingly in demand by makers of polystyrene plastics, synthetic rubbers and resins and other basic industrial materials (THE CHEMICAL AGE, 15 September). This intermediate had previously been made in bulk as a petroleum derivative in the UK, the chief sources being US and Germany.

The plant, on the south side of the Firth of Forth, some 25 miles from Edinburgh and Glasgow, is close to the works of BP Refinery (Grangemouth) Ltd. (a subsidiary of The British Petroleum Co. Ltd.) and adjacent to the plant built by British Hydrocarbon Chemicals Ltd. for the production of chemicals from petroleum.

Basic raw materials used by Forth Chemicals in making styrene monomer are benzene and ethylene, the latter being piped from the BHC plant.

Materials taking part in the pro-

cesses are all liquids or gases which are handled by pumps or compressors. The scale of operation, the nature of the chemical changes taking place and the strict specifications to be followed for the intermediate and the finished styrene demand the use of continuous automatically controlled processes.


According to information given by Forth Chemicals Ltd., all the plants at Grangemouth are outstanding examples of modern practice; the investment in equipment and instruments for each person is high.

Design work was carried out by the engineering department of Monsanto Chemicals Ltd. which also supervised the construction of the plant (erection contractors Costain-John Brown Ltd. and Matthew Hall & Co., Ltd.). The original plant came into full production in April 1953 but to meet the continually increasing demand for styrene monomer the design of an expansion to double the capacity was started in 1954. Later this was increased.

Styrene monomer first came into prominence as an essential raw material for GR-S synthetic rubber, though the original reason for the formation of Forth Chemicals is the manufacture of polystyrene moulding crystals. As an intermediate it is used in dyestuffs, agricultural chemicals and pharmaceuticals; and also in emulsion for paints, textiles, papercoatings, bonding and laminating agents; low pressure mouldings; shoe solings; conveyor belts, cable sheathings, flooring tiles; air-drying enamels; ion exchange resins used as refining agents and catalysts; protective colloids.

This range of products underlines the importance of styrene monomer as a basic chemical in bulk production; equally it shows how far-reaching is the petrochemical industry and how essential to the development of this industry is an uninterrupted flow of the raw material—oil.

New distillation area at Grangemouth.
At right is the distillation area of the original plant. The columns of the new unit are said to be the largest made in this country



Chemist's Bookshelf

ORGANO-METALLIC COMPOUNDS. By G. E. COATES. Methuen & Co. Ltd., London; John Wiley & Sons, New York. 1956. Pp. 197. 12s. 6d.

In view of the current theoretical and technological interest in organo-metallic compounds the appearance of this little book will be welcomed. The author has wisely confined his treatment to those compounds which contain only metal-carbon bonds. Thus, organometallic structures of the metal salt type, as well as most classes of co-ordination and chelate compounds have been omitted. No attempt has been made to include the extensive chemistry of the semi-metals, silicon, phosphorus, arsenic, selenium and tellurium. The book nevertheless systematically covers a wide field of chemistry from group I to group VI in the Periodic Table. While the emphasis throughout is primarily preparative, the underlying treatment is fundamental and many points of theoretical interest are made. Particularly valuable features are the tables of physical data and the extensive bibliography.

Parts of the book will be familiar ground to those readers already well acquainted with organo-metallic compounds. The sections devoted to the elements of groups III and IV, however, provide a wealth of new material of great contemporary interest and commend themselves particularly to the reviewer. Coverage of the transition elements is necessarily brief in a book of this compactness, but fully adequate treatment is accorded the cyclopentadienyls, the valence structure of which is discussed in some detail. The author is to be congratulated on the timely production of a concise yet comprehensive work which is within the reach of every academic purse.

J. H. TURNBULL

FLUIDIZATION. Edited by DONALD F. OTHMER. Rheinhold Publishing Corp., New York; Chapman & Hall Ltd., London. 1956. Pp. 231. 56s.

Subject matter of this book is based upon seven papers presented at a symposium on fluidisation organised jointly by the Polytechnic Institute of Brooklyn and the American Institute of Chemical Engineers. At the time of presentation (February 1955) the theoretical aspects of fluid dynamics and heat and mass transfer in fluid-solid systems were omitted from the symposium but in the subsequent preparation of the papers for publication in book form, additional chapters on these subjects have been prepared.

The book contains nine chapters, the first two (Fluid Dynamics by R. F. Benenati and Heat and Mass Transfer by J. C. Chu) being critical reviews of the literature on the subjects, the following seven being the original lectures presented by outstanding authorities from industry. Chapter 3 by F. A. Zenz presents an analysis of pressure drop and fluid velocity relation-

ships in packed beds in an unusual form intended to facilitate design calculations for, and analysis of, operating units. The usage of such terms as 'phase-diagram' for 'pressure drop—vapour velocity' diagrams and the small scale on which the diagrams are presented detract from an otherwise interesting treatment.

In chapter 4 E. J. Gohr gives a brief account of the background, history and future of fluidisation, while chapter 5 by R. M. Bruce and A. A. Fried deals with the operation of fluidisation processes. This chapter is of particular interest since it contains a critical appraisal of the effect of operating variables. The development of fluid coking is described by R. W. Krebs in chapter 6 with some operating details of particular interest to petroleum technologists. Design and control techniques in moving solids bed systems are discussed by C. Berg in chapter 7. Although much of this chapter is not strictly applicable to fluidised systems, the detailed account of control devices, flow valves, flow controllers, etc., is of considerable interest to students as well as to practising chemical engineers.

Chapter 8 by W. W. Kraft, N. Ulrick and W. O'Connor examines the significance of details in FCC units, particularly engineering design, instrumentation and operation, and contains subject matter of real value to workers concerned in the development of a fluidised technique to new problems. Finally chapter 9 contains an account by R. B. Thompson of the apparatus of fluidisation in the chemical industry with particular reference to the FluoSolids processes for roasting of pyrites and zinc sulphide and for the sizing, drying and heat treatment of solids.

Naturally much of the subject matter of chapters 3 to 8 is drawn from the fluidised cracking units of the petroleum industry but the information and discussion is of interest to workers in other fields. There are, however, serious gaps in the treatment such as, for instance, the lack of any discussion on the design or operating characteristics of cyclone separators, or the omission of a description of pilot plant equipment and methods of scaling up from pilot plant to full scale operations.

Nylon Ropes

A BOOKLET about nylon ropes, illustrated with photographs, has been published by British Nylon Spinners Ltd. It contains a summary of the properties such as high tensile strength, high shock resistance and great flexibility which combine to make nylon suitable for ropes. But the greater part is devoted to factual reports describing specific instances in which nylon has reduced costs, eased handling problems or increased efficiency.

MONDAY 12 NOVEMBER

RIC (London Section)

London: Woolwich Polytechnic SE18, 7.30 p.m. 'Plant Growth-Regulating Substances,' by Professor R. L. Wain.

CS (Leeds Section)

Leeds: Chemistry Lecture Theatre, The University, 6.30 p.m. 'Determination of Alcohol in Blood and Urine of Drunken Drivers and the Interpretation Thereof,' by Dr. D. W. Kent Jones.

CS (Newcastle & Durham)

Durham: Science Laboratories, The University, 5.15 p.m. 'Organic Semi-conductors' by Professor D. D. Eley.

CS (South Wales Section)

Cardiff: Chemistry Department, University College, 5.30 p.m. 'Some Radical Reactions' by Dr. R. N. Haszeldine.

SCI (London Section)

London: 14 Belgrave Square SW1, 6.30 p.m. Jubilee Memorial Lecture: 'The Study of Biologically-Active Agents as a Vocation' by Professor F. Bergel.

Institute of Metals (Scottish Section)

Grangemouth: 2.30 p.m. Visit to works of British Hydrocarbon Chemicals Ltd.

TUESDAY 13 NOVEMBER

Royal Society of Arts

London: John Adam Street, Adelphi, London WC2, 5.15 p.m. 'Chemistry and the Sugar Cane' by Professor L. F. Wiggins.

SCI (Chemical Engineering Group)

London: 14 Belgrave Square, London SW1, 5.30 p.m. 'The Manufacture of Phthalic Anhydride by the Fluidised-Catalyst Method' by H. L

Society for Analytical Chemistry

Birmingham: The University, 7 p.m. Discussion: 'Laboratory Planning and Organisation' opened by C. L. Prior and D. Barkaway.

Inst. of Metals (S. Wales Section)

Swansea: Electricity Showrooms, Kingsway, 6.45 p.m. 'Fuel' by C. A. J. Plummer.

WEDNESDAY 14 NOVEMBER

RIC (London Section)

London: Institute of Metals, 4 Grosvenor Gardens SW1, 6.30 p.m. Annual general meeting followed by film display.

CS (Manchester Section)

Manchester: College of Technology, 6.30 p.m. 'Recent X-ray Structural Determinations in Glasgow' by Professor J. M. Robertson.



Institution of Chemical Engineers

Birmingham: Midlands Institute, Paradise Street, 6.30 p.m. 'The Transport, Storage and Handling of Hydrochloric, Nitric and Sulphuric Acids' by Dr. H. Saenger.

SCI (Food Group)

Mitcham: James Pascall Ltd., 6.30 p.m. Annual conversazione.

SAC (Biological Methods Group)

London: 'The Feathers,' Tudor Street EC4, 6.30 p.m. Discussion: 'Biological Methods in the General Analytical Laboratory.'

University of London

London: School of Pharmacy, 17 Bloomsbury Square WC1, 5.30 p.m. First of two lectures on 'The Contributions of Pharmacy and Chemical Engineering to World Needs' by Brigadier-General Sir Harold Hartley.

Institute of Fuel (NW Section)

Manchester: Engineers' Club, Albert Square, 2.30 p.m. 'Design and Performance of Modern Gas Cleaning Equipment' by C. J. Stairmand.

British Colour Makers' Association

London: May Fair Hotel, 7 for 7.30 p.m. Annual Dinner.

THURSDAY 15 NOVEMBER

RIC (Kent Sub-Section)

Dartford: North-West Kent College of Technology, Miskin Road, 7.30 p.m. 'Melting and Crystal Structure' by Professor A. R. Ubbelohde.

CS (London Section)

London: Burlington House WI, 7.30 p.m. Meeting for the reading of original papers specially arranged to commemorate the 70th birthday of Sir Ian Heilbron.

CS (Bristol Section)

Bristol: Senior Common Room, The University, 5.30 p.m. Social evening, jointly with RIC and SCI.

CS (Leeds Section)

Leeds: Chemistry Lecture Theatre, The University, 6.30 p.m. 'Tropylium' by Professor M. J. S. Dewar.

CS (N Ireland Section)

Belfast: The Queen's University, 7.15 p.m. 'Recent Advances in Acetylene Chemistry' by Professor R. A. Raphael.

CS (Sheffield Section)

Sheffield: Chemistry Lecture Theatre, The University, 7.30 p.m. 'Chemotherapeutic Research' by Dr. F. L. Rose.

SCI (Agriculture & Microbiology Groups)

London: 14 Belgrave Square SW1, 6.15 p.m. 'Plant Virus Diseases' by F. C. Bawden; 'Viruses Attacking Insects' by Dr. K. M. Smith.

I.Chem.E. (Graduates & Students Section)

Manchester: College of Science & Technology, 6.45 p.m. 'Submerged Combustion Evaporators' by J. Austin.

Society for Analytical Chemistry

Liverpool: ICI Metals Division, Kirkby, 2 p.m. Visit.

University of London

London: School of Pharmacy, 17 Bloomsbury Square WC1, 5.30 p.m. Second of two lectures on 'The Contributions of Pharmacy and Chemical Engineering to World Needs' by Brigadier-General Sir Harold Hartley.

FRIDAY 16 NOVEMBER

CS (Birmingham Section)

Birmingham: Chemistry Department, The University, 4.30 p.m. 'Topology and Chemistry' by Dr. A. F. Wells.

CS (Bristol Section)

Bristol: Chemistry Department, The University, 5 p.m. 'Overcrowded Molecules' by Professor C. A. Coulson.

CS (Cambridge Section)

Cambridge: University Chemical Laboratory, Lensfield Road, 8.30 p.m. 'Solutions in Sulphuric Acid' by Dr. R. J. Gillespie.

CS (Glasgow Section)

Glasgow: Chemistry Department, The University, 7.15 p.m. 'The Hydrogen Isotope Effect in Reaction Kinetics' by R. P. Bell.

CS (Newcastle & Durham)

Newcastle-upon-Tyne: Chemistry Building, King's College, 5.30 p.m. Bedson Club Lecture: 'The Chemistry of Some Naturally Occurring Polyacetylenes' by Professor B. Lythgoe.

CS (S Wales Section)

Swansea: Chemistry Department, University College, 6 p.m. 'Some Recent Developments in Inorganic Stereochemistry' by Professor R. S. Nyholm.

CANADIAN CHEMICAL EXPANSION

Outpacing Growth of General Industry by Wide Margin

BY 1975 it is estimated that the Canadian chemical industry could represent a \$4,000 million market in the country. The chemical industry is outpacing the growth of general industry by a wide margin.

The \$4,000 million figure was given by Mr. J. A. Davis, manager of the chemical department of du Pont of Canada, before the annual meeting of the Chemical Market Research Association in Quebec. Although the level was more than three times greater than the current demand, it appeared to be reasonable, he said, as per capita consumption would be only \$140 at that time compared to the current US per capita consumption of \$135.

The natural resources industries of agriculture, mining and forest products will continue to have a major impact on the demand for chemicals, said Mr. Davis. Current agricultural chemical demand amounts to \$75 million, consisting of one half fertiliser and one half pest control and food supplements. It is estimated that the agricultural demand will increase to \$200 million by 1975.

The second sector of the natural resources group, forest products, has a most important effect on chemical demand. It would appear that chemical consumption will increase faster than output of forest products as a result of new pulp cooking processes, improved brightness requirements and combinations of cellulose fibres with other materials to achieve new properties for new end uses.

Under these conditions the demand is estimated to increase from the current \$50 million level to \$110 million in the next two decades.

Also speaking at the meeting, Mr. L. Hynes, vice-president of Canadian Industries Ltd., said: 'My conclusions will be that Canadian consumers of the heavy inorganic chemicals will continue in the future, as in the past, to be supplied largely from domestic sources. The Canadian chemical industry's rapid post-war diversification into the synthetic organics, on the other hand, is unlikely to continue at its recent rate, and a large, though slowly diminishing, proportion of the Canadian market will therefore continue to be supplied by imported chemicals in this category.

Dr. R. S. Jane, president of Shawinigan Chemicals Ltd., declared: 'In my opinion Canadian management must exhibit more faith and confidence in the days that lie ahead than has been the case in the past in this matter of research. I realise how difficult is the decision to authorise the expenditure of relatively large sums on research and development when the risks are so great, but the alternatives are equally hazardous.

'If we in this country require further proof of the necessity for research at this stage in our history it may be found in the annual reports of many of the successful chemical corporations in the United States and United Kingdom where it is frequently stated that more than 50 per cent of the annual income is derived from processes and products that were developed in their research laboratories in the late '30s or early '40s.'

Spanish Projects

Government Grants Aid Chemical Industry Build Up

EXPANSION of the chemical industry in Spain, aided by Government grants and foreign investments, is taking place. Existing capacities are being increased and new plants installed.

For instance, the Union Española de Explosivos SA of Madrid and the Sociedad Iberica de Nitrogenos intend setting up a fertiliser plant to produce 25,000 tons of nitrogen, 25,000 tons of potash and 30,000 tons of phosphate annually. Urea, calcium phosphate and potassium sulphate will also be produced.

Union Española de Explosivos, the largest concern producing superphosphate in Spain, is to increase sulphuric acid production capacity to about 105,000 tons (100 per cent H2SO4) a year. At Cartagena the company expects by next year to have increased production to 185 kg. per hour of nitroglycerine destined for the manufacture of dynamite 2E and 3D.

Liquid Carbonic Anhydride

A liquid carbonic anhydride plant will be installed by the Eulogia Dominguez Company at Creuse. It should be completed by 1958. Ahalla-Oxigeno Linde SA, Baileu, Barcelona, will increase argon production capacity to 30,000 cubic metres per year, and will also develop production of liquid oxygen, nitrogen and other gases with the aid of investments amounting to 6 million pesetas.

In the petrochemicals field, Union Quimica de Norte de España, has obtained licences to import 18,000 tons of crude petroleum for the production of ethylene, propylene, butylene and methane. This company has a production capacity of 1,500 to 3,000 tons a year for titanium dioxide.

Etino Quimica of Barcelona is already manufacturing polystyrene at Monson and will increase production of this plastic. The company is also to undertake production of p.v.c. under licence from Monsanto of

It is understood that Seda de Barcelona SA has interested Dutch AKU in starting production of polyamides and of synthetic fibres having polyamide bases. Initial capacity will be 1,200 tons a year.

Plans are under way for expansion of synthetic rubber plants, and to this end alcohol production was increased to 8,000 tons a year for 1955.

Lithium deposits discovered in Spain may be exploited in collaboration with a US company.

PLASTICS INDUSTRY IN AUSTRALIA

IT IS ESTIMATED that the 1956 value of plastics produced in Australia will exceed £26 million and amount to some 13,000 tons. According to the Australian Financial Review such a production represents more than 50 per cent of Australian plastics require-Expansion plans already under way will continue to reduce dependence on imported raw materials and imported articles containing plastics. The manufacture and processing of plastics in Australia is not, in the main, feasible, because of the small local market and the large scale on which chemical manufacture must be based for economic output. Costs of labour and materials are also high and prospects for plastics exports are limited. The industry is, in fact,

totally dependent on tariff protection. Australian consumption of polythene is about 2,000 tons a year and is increasing rapidly. This plastic is not yet manufactured in Australia but a company there has announced its intention to manufacture it shortly. Ethylene gas is obtainable in Australia from alcohol produced by fermentation of molasses or from oil refining. There are several plastics, however, which Australia may not find it economic to produce for some time. Thus present imports of acrylics are of the order of 700 tons a year. Small, but increasing quantities, of nylons, epoxy resins, special celluloses, polyurethane etc., are imported, but there would be no economic grounds for their production for a long time hence.

AUTRONIC SYSTEM AVAILABLE

All-Electronic Control for Instrumentation

NOW AVAILABLE throughout Europe and the Commonwealth (except Canada) from Elliott Brothers (London) Ltd. is the Swartwout autronic system of control. It is the first miniature all-electronic control system for process and power instrumentation and one of the most flexible in existence with its ability to use a.c., d.c., or motion inputs, as well as conventional primary elements.

Since all transmission of measurement data and transmission of control impulses is made electrically, all restrictions on location of the controller and the recorder or indicator are eliminated as well as restrictions on distance between measurement transmitter and controller, and between controller and power relays.

The complete system comprises: Primary element transmitter, recorder or indicator, controller, manual control, and power relay.

Temperature is measured by a resistance Mentrometer connected into a fixed bridge circuit. Temperatures as low as -100°F and up to 1,200°F can be measured with an accuracy of ±1 per cent. Special transmitters for higher temperatures such as furnace temperatures may be used. Liquid level and flow are measured with an accuracy of ±1 per cent by a diaphragm or bellows element with very small deflection operating the core of a differential transformer, output of which is 0 to 0.500 volts a.c. for full span. Recorder, indicator and controller are easily adapted to the measurement and control of any measured variable that can be connected into a 60-cycle, a.c. voltage. The manual control panel is entirely independent of the recorder and controller

Superiority of the autronic system over the more usual pneumatic equipment has been fully proved in many refinery and other continuous processes. High speed of response is combined with high sensitivity, ensuring that corrective action is taken immediately a process variable starts to deviate from the control point, and before the deviation is visible on the recorder or indicator. Both recorder and controller units are of plug-in design and are easily replaceable.

To ensure satisfactory maintenance of this new control equipment, Elliott Brothers (London) Ltd, will be starting shortly a special training course for service engineers.

CONTRACTS ZIRCONIUM

ACCORDING to the Technical Information and Documents Unit of DSIR the US Atomic Energy Commission has just announced the completion of three new contracts for the supply of zirconium metal for use in nuclear reactors. The amount called for is 2,750 lb. but it is expected that this quantity will probably be increased at a later date.

For use in reactors the zirconium must be produced free from hafnium. The main process for accomplishing this is the Kroll, developed by Dr. Kroll at the US Bureau of Mines claim to have developed new processes which they will use in the new plants being constructed. The Carborundum Co. is extending its present

The division of industrial chemistry, CSIRO, Australia, has been working on the separation of hafnium from zirconium for some time. A secret patent application lodged some time ago has been declassified. The Australian patent depends on the differential reduction of the halides of zirconium and hafnium and the submanufacturers' agents for:

CHINA

M. D. EWART AND CO. LTD

Telephone: Bishopsgate A333 / Teleph sequent disproportionation of the zir-

Pump Control

Aid to Tanker Loading Developed for Far East

REMOTE control equipment has been developed by Shell and the General Electric Co. by means of which a tanker moored at the end of a submarine loading cable 31 miles out at sea can stop the cargo loading pumps on shore.

The equipment, which cost Malayan \$85,000 (£10,000), has been installed at Lutong refinery in Sarawak, British Borneo. The shallowness of the water prevents tankers from coming any nearer than 34 miles.

As the tanker approaches the moorings a portable transmitter/receiver is taken aboard. In addition to providing a radiotelephone service with the shore terminal, this portable set can transmit on a special pump control channel. If it is necessary to stop the pumps in an emergency, the pressing of a control button on the operating panel of the portable set overrides the telephone channel and brings the pump control channel into operation.

Terylene Uses

IT WAS ANNOUNCED at an ICI Ltd. press conference on 31 October that Terylene, produced by Fibre Division, ICI Ltd., is now being used for stockings by leading stocking manufacturers. Terylene is said to be the first important new fibre for stockings to be put on the market for nearly 20 years. Terylene yarns of any particular denier are finer than other yarns of the same denier but are more hardwearing. In addition, they are unaffected by exposure to strong sunlight or by acid atmospheres and diesel fumes. Stockings made from Terylene appear to be more silk-like and are reported by wearers to be warmer.

Birlec Development

A 10-YEAR development plan for Birlec Ltd., makers of dehumidification equipment, has been announced by the company. In connection with

k-----

Commercial Intelligence

The following are taken from the printed reports, but we cannot be responsible for errors that may occur.

Mortgages & Charges

The Companies Consolidation Act of 1908 provides that every Mortgage or Charge, as described herein, shall be registered within 21 days after its creation, otherwise it shall be void against the liquidator and any creditor. The Act also provides that every company shall, in making its Annual Summary, specify the total amount of debt due from the company in respect of all Mortgages or Charges. The following Mortgages or Charges have been so registered. In each case the total debt, as specified in the last available Annual Summary, is also givenmarked with an *-followed by the date of the Summary, but such total may have been reduced.

BRITISH ALUMINIUM CO. LTD., London SW.-1 October, disposition granted in implement of a Trust Deed dated 30 July 1947 etc.; charged on specified property at Kilmallie. *£4,564,508. 22 May 1956.

C. R. BERRETT & Co. LTD., London WC, manufacturers of bitumen etc.-2 October. £300 mortgage, to Arunlex Property Co. Ltd.; charged on land at Wishford Road, Water Ditchampton.

Increases of Capital

SELANGOR OIL PALM CO. LTD. (13,026), 46 Charlotte Square, Edinburgh 2, increased by £76,240, in £1 shares, beyond the registered capital of £83,760.

FLOORLIFE & CHEMICALS LTD. (400,976), 62-3 Fenchurch Street, London EC3, increased by £1,500, in £1 ordinary shares, beyond the registered capital of £1,000.

Change of Name

MELVO LTD., manufacturing druggists, etc., Ogden Lane, Openshaw, Manchester 11, changed to Ogston & Tennant (Aberdeen) Ltd. on 1 October 1956.

Registrations New

J. J. McMahon Ltd.

Private company. (573,723). Registered 1 November. Capital £4,000 in £1 shares. Objects: To carry on the business of wholesale, retail, manufacturing, pharmaceutical, analytical and dispensing chemists and druggists, etc. The permanent directors are: Joseph J. McMahon, 15 Willow Grove, Wallsend; James Sherlock, 1 Woodhead Road, Walker; and Francis P. Sherlock, 20 Links Avenue, Whitley Bay. Secretary: P. Cooper. Solicitors: Waugh Moody & Mulcahy, Newcastle-on-Tyne. Registered office: 5 Higham Place, Newcastle-on-Tyne.

Hoechst Pharmaceuticals Ltd.

Private company. (573,687). Registered 1 November. Capital £10,000 in £1 shares. Objects: To carry on the business of manufacturers of and dealers in drugs, medicines, etc. The subscribers (each with one share) are: Frederic T. Horne and Allan D. M. Phillips, both solicitors, of 2 Bedford Row, London WC1. The first directors are not named. Solicitors: lliffe Sweet & Co., 2 Bedford Row, London WC1.

COMPANY

Wiggins Teape & Co. (1919) Ltd.

Group profit of Wiggins Teape & Co. (1919), paper makers, for halfyear ended 30 June 1956, after providing for debenture interest but before taxation, amounts to £2,373,477. This compares with £2,675,535 (after adjusting proportion of increased charge in obsolescence for 1955) and £2,257,681 for the similar periods of 1955 and 1954 respectively. Interim dividend is being maintained at five per cent on the £8,231,870 ordinary in respect of the year 1956. Despite the lower half-year profits, the board forecasts that the 171 per cent distribution for 1955 will be repeated.

MARKET REPORTS

LONDON Buying interest in the industrial chemicals market has been pretty well maintained during the past week and contract deliveries also continue at a steady level. So far as prices are concerned sulphate of copper has increased to £97 10s per ton less two per cent f.o.b. Liverpool from 2 November and there has been an increase in quotations for white lead and red lead which are currently quoted at £149 15s per ton and £145 per ton respectively. Export enquiry has been on a good scale although keener rates are necessary in the face of increasing competition in overseas markets. There has been a steady demand for the fertiliser materials and both cresylic acid and creosote oil have been in active request.

MANCHESTER The Egyptian situation, so far as the Manchester chemical market is concerned, has been reflected in a little more enquiry for forward delivery during the past week. Meanwhile, contracts in the alkalis and other leading heavy chemicals are being drawn against steadily by industrial consumers. There has been little actual movement of prices, though the general undertone seems to be rather firmer if anything. There has been a moderate aggregate movement of fertiliser materials, with a continued steady call for most of the light and heavy tar products.

GLASGOW Since the last report the Scottish heavy chemical market has remained more or less unchanged. Demand during the past week has continued steady; and business generally has been satisfactory in regard to spot and contract deliveries. important price changes have taken place; on the whole prices have remained firm. The usual enquiries are being received for export, and the market is fairly active.

WILL

Mr. HAROLD LEWIS, F.R.I.C., M.I.Chem.E., of 19 Langley Avenue, Surbiton, Surrey, formerly of Church Lane, Cheshunt, Herts, secretary of Du Pont Co. (United Kingdom) Ltd., who died on 19 May last, left £17,972 5s 2d gross, £10,972 5s 9d net.



"VULCAN" IRON AND STEEL CARBOY HAMPERS SAFETY CRATES, PACKED CARBOYS

HARRIS (LOSTOCK GRALAM) LOSTOCK GRALAM, NORTHWICH, CHESHIRE.


48 x 24

ELECTRICALLY DRIVEN

CENTRIFUGAL

- * Cast iron framing
- * Copper perforated and hooped basket with bronze centre.
- * Copper sheathed spindle and copper safety cover.
- * Mechanical plough with counter balance weight.
- * Scoop controlled fluid coupling.
- * Totally enclosed electric motor.

POTT, CASSELS & WILLIAMSON MOTHERWELL, SCOTLAND



Incidental information

No. 10

items of interest from our laboratory notebooks



Metal indicators have contributed much to the application of Sequestric Acid (EDTA), and H. & W. have made a series of these indicators available. 1-(2-Pyridylazo)-2-naphthol, for example, is used as an indicator in the titration of zinc, copper, and cadmium with Sequestric Acid in the presence of the alkaline earth metals. It is listed under H. & W. Code 7275.3. A description of the methods will be found in a paper by K. L. Cheng and R. H. Bray. Anal. Chem., 27, 782 (1955). available. 1-(2-Pyridylazo)-2-naphthol, for

Tetrahromonhenolohthalein ethyl ester (notassium salt) is an indicator that has been put to a novel purpose. Its exceptionally great 'protein error' affords a method for the detection of proteins. See F. Feigl, Spot Tests, Vol. 2. p., 293. Elsevier Publishing Company (1954). The indicator has recently become available under H. & W. Code 8439.

4-Methylnioxime is the latest reagent for nickel and palladium (see Banks & Hooker, Anal. Chem., 28, 79 (1956)). Nioxime itself has excellent sensitivity for nickel (1 in 10,000,000) but has its shortcomings as a gravimetric reagent. The newcomer is equally sensitive and can be used as a straightforward gravimetric reagent. It can be used in aqueous solution (about 0.3 per cent.). Now listed by H. & W. under Code \$753,



WILLIAMS

Manufacturers of pure chemicals for Research and Analysis

CHADWELL HEATH . ESSEX . ENGLAND

Classified Advertisements

CLASSIFIED RATES: All sections 5d. per word. Minimum 8/-. Three or more insertions 4d. per word. Box Number 2/- extra. Up to mid-day Tuesday for insertion same week.

SEMI-DISPLAY: 30/- per inch. Three or more insertions 25/- per inch.

SUBSCRIPTION: Annual Subscription of 52/6 brings 52 weekly copies of THE CHEMICAL AGE direct to your address from the printer (postage paid by the publishers), and a copy of THE CHEMICAL AGE YEAR BOOK.

COMPANY MEETINGS AND REPORTS: £12.12.0 per column. Three column measure (approximately 360 words).

SITUATIONS VACANT

CHEMIST. A vacancy exists for a young Graduate in Chemistry as Assistant to the Chief Chemist at a large factory in E.10 area. The work involves the development of insulating enamels and varnishes, and offers a most interesting and progressive career to men or women of ability. Please send full details to Personnel Officer, BOX No. C.A. 3509, THE CHEMICAL AGE, 154, FLEET STREET, LONDON, E.C.4.

TECHNICAL SERVICE. A chemist with industrial experience, age 25-32 is required for interesting development work with rapidly growing London company manufacturing wide range of products based on oils, bitumens, natural and synthetic rubbers, vinyl resins etc. The successful applicant will be responsible to the Chief Chemist but will work in close contact with important customers and will be based on the Research Laboratory. Emphasis on experimental ability. Attractive salary. Apply will full details of qualifications and experience to BOX NO. C.A. 3508 THE CHEMICAL AGE, 154, FLEET STREET, LONDON, E.C.4.

OFFICIAL APPOINTMENTS

COUNTY BOROUGH OF BRIGHTON WATERWORKS DEPARTMENT

ASSISTANT CHEMIST AND BACTERIOLOGIST (MALE OR FEMALE)

Applicant should possess either Degree in Chemistry or A.R.I.C. Waterworks experience desirable but not essential. Salary Grade A.P.T. III (£640-£767). Appointment superannuable subject to medical examination

terminable by one month's notice on either side.

Application forms from Waterworks Engineer, 12 Bond Street, Brighton.

W. O. DODD, Town Clerk, BRIGHTON 19th October, 1956.

NORTH WESTERN GAS BOARD MANCHESTER GROUP

Chemist-Rochdale Road Works

Applications are invited for the above pensionable appointment at a salary within Grade A.P.T.7 (£670-£750 p.a.).

Applicants must be experienced in carrying out routine laboratory tests and be able to exercise chemical control of gas manufacturing and product processes. Applicants should possess suitable technical qualifications and gas works experience would be an advantage.

Detailed applications, giving names of two referees, should reach the General Manager, N.W.G.B., Manchester Group Town Hall, Manchester, 2, within 14 days.

OFFICIAL APPOINTMENTS: continued

UNIVERSITY OF DURHAM KING'S COLLEGE, NEWCASTLE-UPON-TYNE Lecturer in Chemical Engineering

The Council of King's College invite applications for a Lecture-ship in Chemical Engineering. Applicants should preferably hold a degree in Chemical Engineering, Chemistry, or Engineering. The initial salary will be fixed at a suitable point on the scale £650×£50—£1,350 in accordance with the qualifications and experience of the successful applicant. Family Allowance and F.S.S.U. Duties to commence early in 1957. Twelve copies of application, together with the names of three persons to whom reference may be made, should be submitted not later than 17th December 1956 to the undersigned from whom

later than 17th December, 1956, to the undersigned from whom further particulars may be obtained.

G. R. HANSON. Registrar of King's College.

FOR SALE

Brand New COCHRAN Vertical and ECONOMIC Self-contained STEAM BOILERS in stock, also all sizes reconditioned and

yalvanteed. List on request.

STAINLESS STEEL TANKS, PANS, CONDENSERS, PLATES, VALVES AND COCKS. Very wide selection.

new ALUMINIUM CONDENSERS, 14 ft. long, 2 ft. 3 in. dia., 386 tubes ½ in. o.d.

white in o.d.

FRED WATKINS (BOILERS). LTD.,

COLEFORD, GLOS.

Phone: Coleford 2271/2.

CHARCOAL, ANIMAL AND VEGETABLE, Horticultural, burning, filtering, disinfecting, medicinal. Also lumps, ground and granulated. THOMAS HILL-JONES, INVICTA WORKS, and granulated. THOMAS HILL-JONES, INVICTA WORKS, BOW COMMON LANE, LONDON, E.3. (TELEPHONE: EAST 3285).

COMPLETE HIGH VACUUM BAND DRYING PLANT BY SCOTT. Drier approximately 35 ft. long, Kek Mill, Powder Dresser, Motor-driven Vacuum Pumps, etc. Cost approximately £20,000. Will accept £3,000 or near offer. Reply: BOX NO. C.A. 3507, THE CHEMICAL AGE, 154, FLEET STREET, LONDON, E.C.4.

MIXERS—1 Baker Hand-tilted Trough, 16 in. by 24 in. by 20 in Fast and loose pulleys and clutch. "Z" blades.

1 Ditto Power-tilted Trough, 30 in. by 20 in. by 24 in. Pulley drive and clutch. Four "L" blades.

THOMPSON & SON (MILLWALL), LTD., LONDON, E.14 **TEL.: EAST 1844**

FOR SALE: continued

PORCELAIN LINED BALL MILL by Torrance, 7ft. 6 in. by 6 ft.

PORCELAIN LINED BALL MILL by Torrance, 7ft. 6 in. by 6 ft. diam. ext. mild steel casing, 16 in. sq. manhole with two strainers. Motorized 400/440/3/50, Charge of flint pebbles included.

SILEX LINED BALL MILL by Glabour, 64 in. diam. by 58 in. ext. mild steel casing, fitted 9½ in. diam., inlet and 17 in. by 12 in. manway. Pulley drive through internal girth gear.

STEEL SILEX LINED BALL MILL, approx. 54 in. by 54 in. diam. inside linings, lining approx. 3 in. thick. Pulley drive through girth year and pinjon. Two rectangular feed onenings with

girth gear and pinion. Two rectangular feed openings with covers and grinding media retaining grids. Pedestal mounted. Grinding charge

PORCELAIN LINED BALL MILL by Steele & Cowlishaw, 24 in.

by 28 in. i.d., with two inlets, covers and sieve plates. Pulley drive. Speed of Mill 30 r.p.m. Charge of procelain balls.

HORIZONTAL CYLINDRICAL STEAM JACKETED VACUUM DRIER, approx. 15 ft. 9 in. by 3 ft. diam., \$\frac{1}{2}\$ in. steel plate construction glanded steam tube and paddle agitator gear driven by F. & L. pulleys. Drier mounted on cradles and with two cultets. two outlets.

HORIZONTAL MIXER by D. Burr, 5 ft. long by 2 ft. wide by 30 in. deep, Fitted spiral type agitator driven by 5 h.p. 400/440/3/50. Motor. Mixer fitted 5 in. sq., bottom centre discharge, slide operated.

NEW STAINLESS STEEL STORAGE VESSELS AND TANKS,

with capacities ranging from 8 gallons to 1,000 gallons.

NEW PORCELAIN AND SILEX LINED BALL MILLS, with capacities ranging from 9 gallons to 260 gallons.

GEORGE COHEN SONS & CO., LTD.

WOOD LANE, LONDON, W.12.

Tel.: Shepherds Bush 2070 and

STANNINGLEY, NR. LEEDS.

Tel.: Pudsey 2241

GARDNER H SIFTER-MIXER, 560 lb. batch. Horizontal 'U'
Trough 66 in. long by 24 in. by 28 in. deep with Revolving
Brush Sifter. Bottom Outlet. Two available.

WINKWORTH MACHINERY LTD. 65, High Street, Staines. Telephone 1010.

MORTON, SON AND WARD, LIMITED, STAINLESS STEEL VESSELS

VESSELS of all shapes and sizes, jacketed or unjacketed-with stainless steel mixing gear to requirements; also stainless steel

storage tanks and vauum vessels.
"MORWOOD" "U"-shaped TROUGH MIXERS—up to 2 tons, in stainless steel, with agitators, scroll or paddle type, jacketed or uniacketed.

Stainless Steel TROUGHS, TANKS and CYLINDERS made to requirements.

These items can also be fabricated in mild steel.

JACKETED PANS

100g., 150g., and 200g., new, in mild steel, for 100 lb. p.s.i. w.p.—with or without mixing gear.

3 cwt. TROUGH MIXERS by CHALMERS and GARDNER

stainless steel-lined troughs.

50g., 75g. and 100g. heavy duty MIXERS by FALLOWS and BATES. Agitators driven through bevel gears from fast and loose pully.

200g. cast-iron JACKETED MIXING VESSEL with nickelchrome impellor type agitator driven through bevel gears from fast and loose pulley.

BROADBENT HYDRO EXTRACTORS

21 in. EQUAL TO NEW, galvanized baskets, electrically driven through centrifugal clutch or belt driven. Safety inter-locks.

AIR COMPRESSORS

THREE 30 c.f.m. at 100 lb. pressure, water cooled, automatic overloads, with or without motors.

AIR RECEIVERS MADE TO REQUIREMENTS PUMPS Selective of the MONO and received head Pumps in stock

Selection of new MONO and second-hand Pumps in stock-2 in. to 5 in.

Inquiries Invited.

MORTON, SON AND WARD, LIMITED, WALK MILL, DOBCROSS, NEAR OLDHAM, Lancs. Phone Saddleworth 437

FOR SALE: continued

PHONE 98 STAINES

ALL STEEL CONDENSER 11 ft. by 2 ft.-68-11 in. diam.

tubes 7ft 8 in. long. 2,400 gall. PRESSURE TANK 24 ft. by 4 ft. 6 in.—125 w.p. 1,750 and 1,350 gall. REC: ALUMINIUM TANKS. 625, 850, 2,000, 2,500, 3,750 and 5,000 gall. GLASS LINED

625, 850, 2,000, 2,500, 3,750 and 5,000 gail. GLASS Little.
TANKS.
"Banbury" Type Twin Blade Jac: PUG MIXERS 18 in. by 12 in. by
20 in.—10 h.p. 400/3/50.
S.S. GARDNER MIXER 40 in. by 17 in. by 17 in.
S.S. 100 gall. JAC: PAN and MIXER 60 and 25 w.p.
S.S. AUTOCLAVE 6 ft. by 3 ft.—100 w.p.
8 ft. 6 in. MONEL CASED WORM CONVEYOR 11 in. diam.
"Z' and FIN BLADE MIXERS, PUMPS, PANS, HYDROS, CONDENSERS, etc.

HARRY H. GARDAM & CO. LTD.

SIMPLITE PUMPS are the World's Simplest, Lightest, Safest and Cheapest diaphragm type. 2 in. Suction completely self priming. Water, mud or chemicals. Petrol, Electric or Hand models from £20. Illustrated leafter from the makers: WM. R. SELWOOD LTD., 3 CHANDLER'S FORD, HANTS. Phone

Two 30 ft. by 9 ft. LANCASHIRE BOILERS for 200 lbs. pressure. Hopkinson Mountings and "Oldbury" Chain Grate Stokers. JAMES DIXON LIMITED, CENTRAL WORKS, BURNLEY.

100 bays of brand new adjustable STEEL SHELVING, 72 in. high by 34 in. wide by 12 in. deep, stove enamelled bronze green. Sent knocked down, 6 shelf bay—£3 15s. 0d. Sample delivered free. Quantity discounts. N. C. BROWN LTD., EAGLE STEELWORKS, HEYWOOD, LANCS. Tel. 69018.

PATENTS & TRADE MARKS

KING'S PATENT AGENCY, LTD., (B. T. King, A.M.I.Mech.E., Patent Agent), 146a, Queen Victoria Street, London, E.C.4. ADVICE Handbook, and Consultation free. Phone: City 6161.

The Proprietor of British Patent No. 625,107 for "METHOD AND MEANS FOR RECTIFICATION AND DISTILLATION OF LIQUIDS WITH LOW TEMPERATURE BOILING POINTS", desires to enter into negotiations with a firm or firms for the sale of the patent or for the grant of licences thereunder. Further particulars may be obtained from Marks & Clerk, 57 & 58, Lincoln's Inn Fields, London, W.C.2.

WORK WANTED & OFFERED

CRUSHING, GRINDING, MIXING and DRYING for the trade. THE CRACK PULVERISING MILLS LTD. Plantation House Mincing Lane, London, E.C.2.

> GRINDING, CRUSHING AND GRADING FINE GRINDING LTD., BLACKHOLE MINE, EYAM TELEPHONE: EYAM 227

PULVERISING of every description of chemical and other materials. Collections, storage, deliveries. THOMAS HILL JONES, LIMITED, INVICTA WORKS, BOW COMMON LANE, LONDON E.3. (TELEPHONE: EAST 3285).

TENDER

TENDERS are invited for the supply of the following lines at TENDERS are invited for the supply of the following lines at British Pharmacopoeia or Codex quality. Prices quoted are to be at landed rates at the port of Fremantle, Western Australia. Tenderers are advised to take into consideration further orders of increased quantities and are requested to state the speed of delivery. ACRIFLAVINE OR PROFLAVINE MERCUROCHROME VIOLA CRYSTALS EXT. IPECAC LIQ, B.P. CALAMINE LODINE

IODINE ZINC OXIDE

ENZOIC ACID BENZOIC ACID LIQ. OPII CONCENTRATE PRO TINCTURE BALSAM TOLUTANUS OR LIQ. TOLUTANUS PRO

SYRUP SQUILL OR EXT. SCILLAE LIQ. POTASSIUM IODIDE BENTONITE

Tenders will close on December 10th, 1956. The lowest or any tender need not necessarily be accepted. Laurent Drug Company, Care Gordon & Gotch (A/sia) Ltd., 21 William Street, Perth, Western Australia.

HEATING TAPES

For many applications

May we help you with your problem?

THE STABILAG CO. LTD.

MARK ROAD . HEMEL HEMPSTEAD

Rockets and **Guided Missiles**

JOHN HUMPHRIES

INTENDED in the main for engineers and technicians, this complete survey of presentday achievements and possible future develop-ments presents the latest information on rocket motors and their applications from an engineer's point of view. Both solid and liquid propellant motors are discussed, the latter more fully as being of greater interest to the engineer. The first half of the book covers propellants, motors and components, the second, the applications of these motors to missiles and aircraft, and in conclusion a review of potentialities for the future is appended. The author has had wide practical experience following a brilliant scholastic career, and is at present actively engaged on rocket research.

31s. (postage paid)

Ernest Benn Limited

Bouverie House ' Fleet Street ' London ' EC4

Classified Advertisement Order Form

To The Manager THE CHEMICAL AGE Bouverie House

Fleet Street, London E.C.4

Please insert the following in your next issue and for weeks thereafter

SITUATIONS VACANT

· EDUCATIONAL

OFFICIAL APPOINTMENTS

- WANTED

FOR SALE

· INVITATION TO TENDER

AUCTIONEERS, VALUERS, etc.

PATENTS

WORK WANTED AND OFFERED

		· ·

CLASSIFIED RATES All sections 5d. per word. Minimum 8/-. Three or more insertions 4d. per word. Box Number 2/- extra. Up to 10 a.m. Tuesday for insertion same week.

SEMI-DISPLAY 30/- per inch. Three or more insertions 25/- per inch.

Address

Petroleum-Derived AROMATIC SOLVENTS

We are now able to obtain supplies of a wide range of Petroleum-derived Aromatic Solvents of very high aromaticity. Typical boiling ranges include 155/174°C., 177/211°C., 197/257°C. and 232/285°C. Other cuts may be available on special request.

Other solvents etc., currently handled in bulk and drums include:

N-BUTANOL ISO-BUTANOL ISO-OCTANOL BUTYL ACETATE XYLOL • ETC

Also available for shipment in bulk special Olefin fractions for chemical synthesis, C6 to C12 range

Enquiries to:

CHEMITRADE LIMITED 17 STRATTON STREET, LONDON, W.I.

Telephone: GROsvenor 3422 Telegrams: MULTIKEM, LONDON Telex: LONDON 8694 TRAFORCHEM



COPPER PLANT

FOR THE
CHEMICAL TRADE

STILLS RECTIFYING COLUMNS CONDENSERS

AUTOCLAVES - CALANDRIAS

VACUUM PANS - BOILING PANS

PIPEWORK COILS, ETC.

ESTABLISHED 1825

BLUNDELL & CROMPTON LTD

WEST INDIA DOCK ROAD . LONDON . E.14

Phone: East 3838 (3 lines) 1408 and 4160 Grams ; Blundell Phane Landon

CHEMICAL PLANT

The Kestner organisation serves many industries. In fact, wherever chemicals are manufactured or used, it is more than likely that you will find some Kestner plant—it may be a stirrer or other small item—it may be a large spray drier or the entire process plant. Whatever it be, large or small, you will find it doing "a good job."

If you are needing any new plant Kestners can help you on any of the following subjects:—

- ACID HANDLING ACID RECOVERY PLANT Pumps, Fans, Pipe Lines, etc.
- DRYING PLANT · EVAPORATION PLANT

 All types A range of plants to suit all Evaporation problems
- FLUID HEAT TRANSMISSION SYSTEMS
- GAS ABSORPTION AND REACTION SYSTEMS
- ISOLETRIC SYSTEM FOR PROCESS HEATING
- KEEBUSH A constructional material resistant to the action of all corrosive liquids
- LABORATORY AND PILOT PLANTS
- STIRRERS AND MIXING EQUIPMENT

Kestner

CHEMICAL



Laboratory Double Effect Evaporator

AMBERLITE

ION EXCHANGE RESINS

Chemicals

for Industry

lon exchange technology has not only earned widespread recognition in water conditioning, where it had its beginnings, but has moved to other fields. Today, the AMBERLITE ion exchange resins serve in the production of pharmaceuticals; aid in the concentration and recovery of metals; deionize syrups; and make possible the analysis, isolation and separation of a host of compounds or elements heretofore considered too elusive for attack by conventional chemical techniques. In all of these applications the AMBERLITE ion exchange resins operate with dexterity and efficiency scarcely approached by older techniques.

Now available from British manufacture are AMBERLITE IR-120 high capacity cation exchanger and AMBERLITE IRA-400 strongly basic anion exchanger.

Detailed information will be sent on request.

CHARLES LENNIG & CO. (GREAT) LTD. 18-20 YORK BUILDINGS ADELPHI LONDON W.C.2

Amberlite is a registered trade mark of our parent company Rohm & Haas Co. Philadelphia